
KSConf Documentation

Release 0.8-beta4.dev16+7426247

Lowell Alleman

Jul 03, 2020

Contents

1	Welcome to KSCONF!	3
2	Install	5
3	User Guide	7
3.1	Introduction	7
3.2	Concepts	8
3.3	Installation Guide	10
3.4	Commands	15
3.5	Cheat Sheet	45
3.6	Contributing	50
3.7	Developer setup	53
3.8	Git tips & tricks	54
3.9	Random	58
3.10	Contact	60
3.11	Command line reference	60
3.12	Changelog	74
3.13	Known issues	85
3.14	Advanced Installation Guide	85
3.15	License	94
3.16	API Reference	98
4	Indices and tables	113
	Bibliography	115
	Python Module Index	117
	Index	119



Author Lowell Alleman (Kintyre)

Version 0.8-beta4

CHAPTER 1

Welcome to KSCONF!

KSCONF is a modular command line tool for Splunk admins and app developers. It's quick and easy to get started with basic commands and grow into the more advanced commands as needed. Thank you for reviewing our expanding body of documentation to help smooth your transition to a more well-managed Splunk environment and explore ways to integrate Ksconf capabilities into your existing workflow.

We are glad you are here! No matter where you're starting from, Ksconf can help. Let us know if there is anything we can do to help along your journey.

– Kintyre team

Ksconf can be directly installed as a Python (via pip) or as a Splunk app. The Splunk app option is often easier.

To install as a **python package**, run the following:

```
pip install kintyre-splunk-conf
```

To install the **Splunk app**, download the latest [KSCONF App for Splunk](#) release. Note that a one-time registration command is needed to make ksconf executable:

```
splunk cmd python $SPLUNK_HOME/etc/apps/ksconf/bin/install.py
```


3.1 Introduction

KSCONF (Kintyre’s Splunk Configuration tool) is a command-line tool that helps administrators and developers manage their Splunk environments by enhancing their ability to control configuration files. By design, the interface is modular so that each function (aka subcommand) can be learned quickly and used independently. Most Ksconf commands are simple enough for a quick one-off job, yet reliable enough to integrate into complex app build and deployment workflow.

Ksconf helps manage the nuances of storing Splunk apps in a version control system, such as git. It also supports pointing live Splunk apps to a working tree, merging changes from the live system’s (local) folder to the version controlled folder (often ‘default’), and in more complex cases, it deals with more than one *layer* of “default”, which Splunk can’t handle natively.

Note: What KSCONF is not

Ksconf does *not* replace your existing Splunk deployment mechanisms or version control tools. The goal is to complement and extend, not replace, the workflow that works for you.

3.1.1 Design principles

Ksconf is a toolbox. Each tool has a specific purpose and function that works independently. Borrowing from the Unix philosophy, each command should do one thing well and be easily combined to handle higher-order tasks.

When possible, be familiar. Various commands borrow from popular UNIX command line tools such as **grep** and **diff**. The modular nature of the command and other design features were borrowed from **git** and **splunk** as well.

Don't impose workflow. Ksconf works with or without version control and independently of your deployment mechanisms. If you are looking to implement these things, Ksconf is a great building block.

Embrace automated testing. It's impractical to check every scenario between each release, but significant work has gone into unit testing the CLI to avoid breakage.

3.1.2 Common uses for Ksconf

- Promote changes from local to default
- Maintain multiple independent layers of configurations
- Reduce duplicate settings in a local file
- Upgrade apps stored in version control
- Merge or separate configuration files
- Git pre-commit hook for validation
- Git post-checkout hook for workflow automation
- Send *.conf* stanzas to a REST endpoint (Splunk Cloud or no file system access)

3.1.3 Getting started

You're in the right place. If you are a beginner, try checking these out first:

- [Cheat Sheet](#) - Like jumping in the deep end, or prefer examples of descriptions? Start here.
- [Concepts](#) - To get a more theoretical background on why these things matter.
- [Commands](#) - Start here if you'd like a more thorough introduction.

3.2 Concepts

3.2.1 Configuration layers

The idea of configuration layers is shared across multiple actions in Ksconf. Specifically, *combine* is used to merge multiple layers, and the *unarchive* command can be used to install or upgrade an app in a layer-aware way.

What's the problem?

In a typical enterprise deployment of Splunk, a single app can easily have multiple logical sources of configuration:

1. Upstream app releases, often from Splunkbase
2. Organization-specific customizations or fixes added by a local developer
3. Fixes to buggy upstream settings, like *indexes.conf*, requested by your Splunk admin

4. Custom knowledge objects created by subject matter experts

Ideally we would like to version control these, but doing so is complicated because normally you have to manage all four of these logical layers in one ‘default’ folder.

Note: Isn’t that what the **local** folder is for?

Splunk requires that app settings be located either in `default` or `local`; and managing local files with version control leads to merge conflicts. So effectively, all version controlled settings need to be in `default`, or risk merge conflicts. However, making changes to the `default` folder causes issues when you attempt to upgrade an app upstream. See how this is a dilemma?

Let’s suppose a new upstream version is released. If you aren’t managing layers independently, then you have to manually upgrade the app, being careful to preserve all custom configurations. Compare this to the solution provided by the *combine* functionality. The layered approach provides an advantage because logical sources can be stored separately in their own directories, thus allowing them to be modified independently. Using this approach, changes in the “upstream” layer will only come from an official release, and the organizational layer will contain customizations made solely by your organization. Practically, this means it’s no longer necessary to comb through commit logs identifying which custom changes need to be preserved and reapplied.

While this doesn’t completely remove the need for a person to review app upgrades, it does lower the overhead enough that updates can be pulled in more frequently, thus minimizing divergence.

3.2.2 Minimizing files

A typical scenario:

To customize a Splunk app or add-on, many admins simply copy the conf file from `default` to `local` and then apply changes to the local copy. That’s a common practice, but stopping there complicates future upgrades. The next step should be to clean up the local file, deleting all the unmodified entries that were copied from `default`.

Why does this matter?

If you’ve copied a default file into the local folder, this means that local file doesn’t contain *only* your settings, it contains a copy of *all* of the default settings too. So in the future, fixes published by the app creator are likely to be masked by your local settings. A better approach is to reduce the local conf file leaving only the stanzas and settings that you intended to change. While this is a monotonous to do by hand, it is easily accomplished by *ksconf minimize*. This makes your conf files easier to read and simplifies upgrades.

What does Splunk have to say about this? (From the docs)

“When you first create this new version of the file, **start with an empty file and add only the attributes that you need to change**. Do not start from a copy of the default directory. If you copy the entire default file to a location with higher precedence, any changes to the default values that occur through future Splunk Enterprise upgrades cannot take effect, because the values in the copied file will override the updated values in the default file.” – [SPLKDOC1]

Tip:

It's a good practice to minimize your files right away. If you wait, it may not be obvious what specific version of default that local was copied from. In other words, if you run the `minimize` command *after* you've upgraded the default folder, you may need to do extra work to manually reconcile upgrade differences, because any changes made between the initial version of the default file and the most recent release of the conf file cannot, be automatically addressed in this fashion. If your files are all in git, and you know a REF of the previous version of your default file, you can use some commands like this:

```
# Review the output of the log, and find the revision of the last change
git log --oneline -- default/inputs.conf

# Assuming "e633e6" was identified as the desired baseline ref, based on the 'log'
↳output

# Compare what's changed in the 'inputs.conf' file between releases (FYI only)
ksconf diff <(git show e633e6:./default/inputs.conf) default/inputs.conf

# Now apply the 'minimization' based on the original version of inputs.conf
ksconf minimize --target=local/inputs.conf <(git show e633e6:./default/inputs.conf)
```

As always, be sure to double check the results.

3.3 Installation Guide

KSCONF can be installed either as a Splunk app or a Python package. Picking the option that's right for you is fairly easy.

Unless you have experience with Python packaging or are planning on customizing or extending Ksconf, then the *Splunk app* is likely the best place for you to start. The native Python package works well for many developer-centric scenarios, but installation ends up being complicated for the more typical admin-centric use-case. Therefore, most users will find it easier to start with the Splunk app.

Note: The introduction of a Splunk app is a fairly new occurrence (as of the 0.6.x release). Originally we resisted this idea, since ksconf was designed to manage other apps, not live within one. Ultimately however, the packaging decision was made to ensure users of all levels can utilize the program, as Python packaging is a mess and can be daunting for the uninitiated.

3.3.1 Overview

Install	Advantages	Potential pitfalls
Python package	<ul style="list-style-type: none"> • Most ‘pure’ and flexible install • One command install. (ideal) • Easy upgrades • More extendable (plugins) • <i>Install Python package</i> 	<ul style="list-style-type: none"> • Lots of potential variations and pitfalls • Many Linux distro’s don’t ship with pip • Must consider/coordinate installation user. • Often requires some admin access. • Too many install options (complexity)
Splunk app	<ul style="list-style-type: none"> • Quick installation (single download) • Requires one time bootstrap command • Self contained; no admin access require • Fast demo; fight with pip later • <i>Install Splunk App</i> 	<ul style="list-style-type: none"> • Crippled Python install (no pip) • Can’t add custom extensions (entrypoints) • No CLI completion (yet) • <i>Grandfather Paradox</i>
Offline package	<ul style="list-style-type: none"> • Security: strict review and change control • <i>Advanced Installation Guide.</i> 	<ul style="list-style-type: none"> • Requires many steps. • Inherits ‘Python package’ pitfalls.

3.3.2 Requirements

Python package install:

- Python Supports Python 2.7, 3.4+
- PIP (strongly recommended)
- Tested on Mac, Linux, and Windows

Splunk app install:

- Splunk 6.0 or greater is installed

3.3.3 Install Splunk App

Download and install the [KSCONF App for Splunk](#). Then open a shell, switch to the Splunk user account and run this one-time bootstrap command.

```
splunk cmd python $SPLUNK_HOME/etc/apps/ksconf/bin/install.py
```

On Windows, open a terminal as Administrator and type:

```
cd "C:\Program Files\Splunk"  
bin\splunk.exe cmd python etc\apps\ksconf\bin\install.py
```

This will add ksconf to Splunk's bin folder, thus making it executable either as ksconf or, less optimally, splunk cmd ksconf. (If you can run splunk without giving it a path, then ksconf should work too.)

At some point we may add an option for you to do this setup step from the UI.

Note: Alternate download

You can also download the latest (and pre-release) SPL from the [GitHub Releases](#) page. Download the file named like ksconf-app_for_splunk-ver.tgz

3.3.4 Install Python package

Quick Install

Using pip:

```
pip install kintyre-splunk-conf
```

System-level install: (For Mac/Linux)

```
curl https://bootstrap.pypa.io/get-pip.py | sudo python - kintyre-splunk-conf
```

Enable Bash Completion

Context-aware autocomplete can be a great time saver. If you're on a Mac or Linux, and would like to enable bash completion, run these commands:

```
pip install argcomplete  
echo 'eval "$(register-python-argcomplete ksconf)"' >> ~/.bashrc
```

(This option is not currently available for Splunk App installs due to a lack of documentation and testing available presently. It should be possible. Pull requests are welcome.)

Ran into issues?

If you encounter any issues, please refer to the [Advanced Installation Guide](#). Substantial time and effort was placed into the assembly of the information based on various scenarios we encountered. A good place to begin would be in the [Troubleshooting](#) section.

3.3.5 Install from GIT

If you'd like to contribute to ksconf, or just build the latest and greatest, then installing from the git repository is a good choice. (Technically this is still installing with pip, so it's easy to switch between a PyPI install, and a local install.)

```
git clone https://github.com/Kintyre/ksconf.git
cd ksconf
pip install .
```

See *Developer setup* for additional details about contributing to ksconf.

3.3.6 Validate the install

No matter how you install ksconf, you can confirm that it's working with the following command:

```
ksconf --version
```

The output should look something like this:

```

                                     #
                                     ##
### ##      ##### ##### ##### ## ## #####
### ##      ### ##          ## ##### ##
#####      ### ##          ## ## ##### #####
### ##      ### ##          ## ## ### ## ##
### ## #####      ##### ##### ## ## ##
                                     #

ksconf 0.7.3 (Build 376)
Python: 2.7.15 (/Applications/splunk/bin/python)
Git SHA1 dc94f811 committed on 2019-06-05
Installed at: /Applications/splunk/etc/apps/ksconf/bin/lib/ksconf
Written by Lowell Alleman <lowell@kintyre.co>.
Copyright (c) 2019 Kintyre Solutions, Inc, all rights reserved.
Licensed under Apache Public License v2

kintyre_splunk_conf (0.7.3)

Commands:
  check          (stable)  OK
  combine        (beta)    OK
  diff           (stable)  OK
  filter         (alpha)   OK
  merge          (stable)  OK
  minimize       (beta)    OK
  promote        (beta)    OK
  rest-export    (beta)    OK
  rest-publish   (alpha)   OK   (splunk-sdk 1.6.6)
  snapshot       (alpha)   OK
  sort           (stable)  OK
```

(continues on next page)

(continued from previous page)

unarchive	(beta)	OK	
xml-format	(alpha)	OK	(lxml 4.2.5)

Missing 3rd party libraries

Note: *Splunk app for KSCONF* users don't need to worry about this.

As of version 0.7.0, ksconf now includes commands that require external libraries. But to keep the main package slim, these libraries aren't strictly required unless you want the specific commands. As part of this change, **ksconf --version** now reports any issues with individual commands in the 3rd column. Any value other than 'OK' indicates a problem. Here's an example of the output if you're missing the splunk-sdk package.

```
...
promote      (beta)      OK
rest-export  (beta)      OK
rest-publish (alpha)     Missing 3rd party module: No module named splunklib.client
snapshot     (alpha)     OK
...
```

Note that while the rest-publish command will not work in the example above, all of the other commands will continue to work fine. If you don't need rest-publish then there's no need to do anything about it. If you want the packages, install the "thirdparty" extras using the following command:

```
pip install kintyre-splunk-conf[thirdparty]
```

Other issues

If you run into any issues, check out the [Validate the install](#) section.

3.3.7 Command line completion

Bash completion allows for a more intuitive and interactive workflow by providing quick access to command line options and file completions. Often this saves time since the user can avoid mistyping file names or be reminded of which command line actions and arguments are available without switching contexts. For example, if the user types `ksconf d` and hits Tab, then the `ksconf diff` is completed. Or if the user types `ksconf`, and hits Tab twice, the full list of command actions are listed.

This feature uses the [argcomplete](#) Python package and supports Bash, zsh, tcsh.

Install via pip:

```
pip install argcomplete
```

Enabling command line completion for kscnf can be done in two ways. The easiest option is to enable it for kscnf only. (However, it only works for the current user; it can break if the kscnf command is referenced in a non-standard way.) The alternate option is to enable global command line completion for all python scripts at once, which is preferable if you use *argparse* for many python tools.

Enable argcomplete for kscnf only:

```
# Edit your bashrc script
vim ~/.bashrc

# Add the following line
eval "$(register-python-argcomplete kscnf)"

# Restart you shell, or just reload by running
source ~/.bashrc
```

To enable argcomplete globally, run the command:

```
activate-global-python-argcomplete
```

This adds a new script to your the `bash_completion.d` folder, which can be used for all scripts and all users, but it does add some minor overhead to each completion command request.

OS-specific notes:

- **Mac OS X:** The global registration option may not work as the old version of Bash was shipped by default. So either use the one-shot registration, or install a later version of bash with homebrew: `brew install bash` then. Switch to the newer bash by default with `chsh /usr/local/bin/bash`.
- **Windows:** Argcomplete doesn't work on windows Bash for GIT. See [argcomplete issue 142](#) for more info. If you really want this, use Linux subsystem for Windows instead.

3.4 Commands

The kscnf command documentation is provided in the following ways:

1. A detailed listing of each sub-command is provided in this section. This includes relevant background descriptions, typical use cases, examples, and discussion of relevant topics. An expanded descriptions of CLI arguments and their usage is provided here. If you have not used a particular command before, start here.
2. The *Command line reference* provides a quick and convenient reference when the command line is unavailable. The same information is available by typing `kscnf <CMD> --help`. This is most helpful if you're already familiar with a command, but need a quick refresher.

Warning: Apologies for the dust

The command docs are currently undergoing reorganization. We're considering a topical layout rather than a per-command layout. Feedback and technical writing / organization contributions are highly welcomed.

Table 1: Command Listing

Command	Maturity	Description
<i>ksconf check</i>	stable	Perform basic syntax and sanity checks on .conf files
<i>ksconf combine</i>	beta	Combine configuration files across multiple source directories into a single destination directory. This allows for an arbitrary number of Splunk configuration layers to coexist within a single app. Useful in both ongoing merge and one-time ad-hoc use.
<i>ksconf diff</i>	stable	Compare settings differences between two .conf files ignoring spacing and sort order
<i>ksconf filter</i>	alpha	A stanza-aware GREP tool for conf files
<i>ksconf merge</i>	stable	Merge two or more .conf files
<i>ksconf minimize</i>	beta	Minimize the target file by removing entries duplicated in the default conf(s)
<i>ksconf package</i>	alpha	Create a Splunk app .spl file from a source directory
<i>ksconf promote</i>	beta	Promote .conf settings between layers using either batch or interactive mode. Frequently this is used to promote conf changes made via the UI (stored in the local folder) to a version-controlled directory, such as default.
<i>ksconf rest-export</i>	beta	Export .conf settings as a curl script to apply to a Splunk instance later (via REST)
<i>ksconf rest-publish</i>	alpha	Publish .conf settings to a live Splunk instance via REST
<i>ksconf snapshot</i>	alpha	Snapshot .conf file directories into a JSON dump format
<i>ksconf sort</i>	stable	Sort a Splunk .conf file creating a normalized format appropriate for version control
<i>ksconf unarchive</i>	beta	Install or upgrade an existing app in a git-friendly and safe way
<i>ksconf xml-format</i>	alpha	Normalize XML view and nav files

3.4.1 ksconf

Ksconf: Kintyre Splunk CONFig tool

This utility handles a number of common Splunk app maintenance tasks in a small and easy to deploy package. Specifically, this tool deals with many of the nuances with storing Splunk apps in git and pointing live Splunk apps to a git repository. Merging changes from the live system's (local) folder to the version controlled (default) folder and dealing with more than one layer of "default" are all supported tasks which are not native to Splunk.

```
usage: kscnf [-h] [--version] [--force-color]
           {check,combine,diff,filter,merge,minimize,package,promote,rest-export,rest-
↪publish,snapshot,sort,unarchive,xml-format}
           ...
```

Named Arguments

--version show program's version number and exit

--force-color Force TTY color mode on. Useful if piping the output a color-aware pager, like 'less -R'

3.4.2 kscnf check

Provides basic syntax and sanity checking for Splunk's .conf files. Use Splunk's built-in `btool check` for a more robust validation of attributes and values.

Consider using this utility as part of a pre-commit hook.

```
usage: kscnf check [-h] [--quiet] FILE [FILE ...]
```

Positional Arguments

FILE One or more configuration files to check. If '-' is given, then read a list of files to validate from standard input

Named Arguments

--quiet, -q Reduce the volume of output.

See also:

Pre-commit hooks

See [Pre-commit hooks](#) for more information about how the check command can be easily integrated in your git workflow.

How 'check' differs from btool's validation

Keep in mind that idea of *valid* in kscnf is different than within Splunk. Specifically,

- **Kscnf is more picky syntactically.** Dangling stanzas and junk lines are picked up by kscnf in general (the 'check' command or others), but silently by ignored Splunk.
- **Btool handles content validation.** The `btool check` mode does a great job of checking stanza names, attribute names, and values. Btool does this well and kscnf tries to not repeat things that Splunk already does well.

Why is this important?

Can you spot the error in this props.conf?

```
1 [myapp:web:access]
2 TIME_PREFIX = \[
3 SHOULD_LINEMERGE = false
4 category = Web
5 REPORT-access = access-extractions
6
7 [myapp:total:junk
8 TRANSFORMS-drop = drop-all
```

That's right, line 7 contains the stanza `myapp:total:junk` that doesn't have a closing `]`. How does Splunk handle this? It ignores the broken stanza header completely and therefore `TRANSFORMS-drop` gets added to the `myapp:web:access` sourcetype, which will likely result in the loss of data.

Splunk also ignores entries like this:

```
EVAL-bytes-(coalesce(bytes_in,0)+coalesce(bytes_out,0))
```

Of course here there's no `=` anywhere on the line, so Splunk just assumes it's junk and silently ignores it.

Tip: If you want to see how different this is, run `ksconf check` against the system default files:

```
ksconf check --quiet $SPLUNK_HOME/etc/system/default/*.conf
```

There's several files that ship with the core product that don't pass this level of validation.

Note: Key concepts

Before diving into the `combine` command, it may be helpful to brush up on the concept of *configuration layers*.

3.4.3 ksconf combine

Merge `.conf` settings from multiple source directories into a combined target directory. Configuration files can be stored in a `/etc/*d` like directory structure and consolidated back into a single 'default' directory.

This command supports both one-time operations and recurring merge jobs. For example, this command can be used to combine all users' knowledge objects (stored in 'etc/users') after a server migration, or to merge a single user's settings after their account has been renamed. Recurring operations assume some type of external scheduler is being used. A best-effort is made to only write to target files as needed.

The ‘combine’ command takes your logical layers of configs (upstream, corporate, Splunk admin fixes, and power user knowledge objects, ...) expressed as individual folders and merges them all back into the single default folder that Splunk reads from. One way to keep the ‘default’ folder up-to-date is using client-side git hooks.

No directory layout is mandatory, but taking advantages of the native-support for ‘dir.d’ layout works well for many uses cases. This idea is borrowed from the Unix System V concept where many services natively read their config files from `/etc/*.d` directories.

Version notes: `dir.d` was added in `ksconf` 0.8. Starting in 1.0 the default will switch to ‘dir.d’, so if you need the old behavior be sure to update your scripts.

```
usage: ksconf combine [-h] [--target TARGET] [-m {auto,dir.d,disable}]
                    [-I PATTERN] [-E PATTERN] [--dry-run] [--follow-symlink]
                    [--banner BANNER] [--disable-marker]
                    source [source ...]
```

Positional Arguments

source The source directory where configuration files will be merged from. When multiple source directories are provided, start with the most general and end with the specific; later sources will override values from the earlier ones. Supports wildcards so a typical Unix `conf.d/##-NAME` directory structure works well.

Named Arguments

--target, -t Directory where the merged files will be stored. Typically either ‘default’ or ‘local’

-m, --layer-method Possible choices: `auto`, `dir.d`, `disable`

Set the layer type used by SOURCE.

Use `dir.d` if you have directories like `MyApp/default.d/##-layer-name`, or use `disable` to manage layers explicitly and avoid any accidental layer detection. By default, `auto` mode will enable transparent switching between ‘dir.d’ and ‘disable’ (legacy) behavior.

-I, --include Name or pattern of layers to include.

-E, --exclude Name or pattern of layers to exclude from the target.

--dry-run, -D Enable dry-run mode. Instead of writing to TARGET, preview changes as a ‘diff’. If TARGET doesn’t exist, then show the merged file.

--follow-symlink, -l Follow symbolic links pointing to directories. Symlinks to files are always followed.

- banner, -b** A banner or warning comment added to the top of the TARGET file. Used to discourage Splunk admins from editing an auto-generated file.
- For other on-going *combine* operations, it's helpful to inform any .conf file readers or potential editors that the file is automatically generated and therefore could be overwritten again. For one-time *combine* operations, the default banner can be suppressed by passing in an empty string (' ' or "" on Windows)
- disable-marker** Prevents the creation of or checking for the .ksconf_controlled marker file safety check. This file is typically used indicate that the destination folder is managed by ksconf. This option should be reserved for well-controlled batch processing scenarios.

You may have noticed similarities between the *combine* and *merge* subcommands. That's because under the covers they are using much of the same code. The *combine* operation essentially does a recursive merge between a set of directories. One big difference is that *combine* command will handle non-conf files intelligently, not just conf files. Additionally, *combine* can automatically detect layers for you, depending on the layering scheme in use.

Mixing layers

Just like all layers can be managed independently, they can also be combined in any way you would like. This also allows for different layers to be mixed-and-matched by selectively including layers to combine. This feature is now available in ksconf 0.8.0 and later using the `--include` and `--exclude` CLI options, which should behave as just as you'd expected.

Note: A more detailed explanation

The `--include` and `--exclude` arguments are processed in the order given. These filters are applied to all layer names. The last match wins.


If `--include` is first, then by default all layers, except for the ones explicitly included, will be excluded. Conversely, if `--exclude` is first, then all layers will be included except for the ones explicitly included. If *no* filters are given then all layers will be processed.

Here's an example, truncated for brevity, to further demonstrate how this can be used practically:

```
Splunk_TA_nix/
├── README.txt
├── bin
│   ├── bandwidth.sh
│   └── common.sh
├── default.d
│   ├── 10-upstream
│   │   ├── app.conf
│   │   └── data
│   │       └── ui
```

(continues on next page)

(continued from previous page)



Here we have several named layers in play:

- 10-upstream - the layer used to contain the default app content that ships from the Splunk TA, or whatever is “upstream” source is.
- 20-common - organizational level change to deployed everywhere.
- 30-master-apps - The bits that should just go to the indexers.
- 30-shcluster-apps - Content that should go to just the search heads.

In this case, we always want to combine the 10-* and 20-* layers, but only want to include either the master or searchhead cluster layer depending on server role.

```

ksconf combine src/Splunk_TA_nix --target build/shcd/Splunk_TA_nix \
  --exclude=30-* --include=30-shcluster-apps
ksconf combine src/Splunk_TA_nix --target build/cm/Splunk_TA_nix \
  --exclude=30-* --include=30-master-apps

# Say you just want the original app, for some reason:
ksconf combine src/Splunk_TA_nix --target /build/orig/Splunk_TA_nix --include=10-upstream

```

Using this technique you can pretty quickly write some simple shell scripts to build these all at once:

```

for role in shcluster master
do

```

(continues on next page)

(continued from previous page)

```
ksconf combine src/Splunk_TA_nix \  
  --target build/${role}/Splunk_TA_nix \  
  --exclude=30-* --include=30-${role}-apps  
done
```

Hopefully this gives you some ideas on how you can start to build some custom workflows with just a few small shell scripts.

Layer methods

Ksconf supports different methods of layer detection mechanism. Right now just two different schemes are supported, but if you have other ways of organizing your layers, please *reach out*.

Directory.d (dir.d) Also known as *.d directory layout is allows layers to be embedded on a directory structure that allows for simple prioritization and labels to be applied to each layer. Anyone who's configured a Linux server should find this familiar.

Example: MyApp/default.d/10-my_layer/props.conf

Convention: <directory-name>.d/<##>-<layer-name>/

When these layers are combined, the top level folder is modified to remove the trailing .d, and all content from the enable layers is combined within that folder. The layer-name portion of the path is discarded in the final combined path. Content is combined based on the assigned ranking of each layer, or directory sort order.

Disable (legacy) If you would prefer to stick with the previous behavior (no automatic detection of layers) and specify all *SOURCE* directories manually, then use this mode. In this mode, each layer must be explicitly defined (or provide as a wildcard) and any other files operations must be handled elsewhere.

Auto (default) In auto mode, if more than one source directory is given, then disable mode is used, if only a single directory is given then dir.d will be used.

How do I pick?

Mode	Useful when	Avoid if
dir.d	<ul style="list-style-type: none"> • Building a full app • If you need layers in multiple places (default.d, and lookups.d) • If you sometimes have no layers, then combine falls back to a file copy 	<ul style="list-style-type: none"> • Have existing .d folders with other meaning • Have multiple source directories.
disable	<ul style="list-style-type: none"> • Highly customized work flows / full-control over combination logic 	<ul style="list-style-type: none"> • For app build scripts.

Examples

Merging a multilayer app

Let's assume you have a directory structure that looks like the following. This example features the Cisco Security Suite.


```

Splunk_CiscoSecuritySuite/
├── README
├── default.d
│   ├── 10-upstream
│   │   ├── app.conf
│   │   ├── data
│   │   │   └── ui
│   │   │       ├── nav
│   │   │       │   └── default.xml
│   │   │       └── views
│   │   │           ├── authentication_metrics.xml
│   │   │           ├── cisco_security_overview.xml
│   │   │           ├── getting_started.xml
│   │   │           ├── search_ip_profile.xml
│   │   │           ├── upgrading.xml
│   │   │           └── user_tracking.xml
│   ├── eventtypes.conf
│   ├── macros.conf
│   ├── savedsearches.conf
│   └── transforms.conf
├── 20-my-org
│   └── savedsearches.conf
├── 50-splunk-admin
│   ├── indexes.conf
│   ├── macros.conf
│   └── transforms.conf
└── 70-firewall-admins

```

(continues on next page)

(continued from previous page)



In this structure, you can see several layers of configurations at play:

1. The `10-upstream` layer appears to be the version of the default folder that shipped with the Cisco app.
2. The `20-my-org` layer is small and only contains tweaks to a few saved search entries.
3. The `50-splunk-admin` layer represents local settings changes to specify index configurations, and to augment the macros and transformations that ship with the default app.
4. And finally, `70-firewall-admins` contains some additional view (2 new, and 1 existing). Note that since `user_tracking.xml` is not a `.conf` file it will fully replace the upstream default version (that is, the file in `10-upstream`)

You can merge all these layers inside this app into a new app folder using the command below:

```
ksconf combine repo/Splunk_CiscoSecuritySuite --target=shcluster/apps/Splunk_
↳CiscoSecuritySuite
```

`ksconf` will automatically detect the `default.d` folder as a layer-containing directory and merge content from the detected layers (`10-upstream`, `20-my-org`, ...) into a new `default` folder in the resulting app. All other content (such as `README`, `bin`, `static`, `lookups` and so on) will be copied as-is.

Changed in version 0.8: If you are using `ksconf` before 0.8, then you have to manually merge the layers, and possibly copy other top-level folders on your own (outside of `ksconf`). The example below still works fine after version 0.8, but the default behavior may change in 1.0, so it's advisable to start using `--layer-method` explicitly in any scripts you may use.

Here are the commands that could be used to generate a new (merged) `default` folder from all of the layers shown above.

```
cd Splunk_CiscoSecuritySuite
ksconf combine default.d/* --target=default
```

Note that in the example above, the `default` folder now lives along side the `default.d` folder. Also note that *only* the contents of `default.d` are copied, not the entire app, like in the above example.

See also:

The `unarchive` command can be used to install or upgrade apps stored in a version controlled system in a layer-aware manor.

Consolidating ‘users’ directories

The `combine` command can consolidate ‘users’ directory across several instances after a phased server migration. See *Migrating the ‘users’ folder*.

3.4.4 `ksconf diff`

Compares the content differences of two `.conf` files

This command ignores textual differences (like order, spacing, and comments) and focuses strictly on comparing stanzas, keys, and values. Note that spaces within any given value, will be compared. Multi-line fields are compared in a more traditional ‘diff’ output so that long saved searches and macros can be compared more easily.

```
usage: ksconf diff [-h] [-o FILE] [--comments] CONF1 CONF2
```

Positional Arguments

CONF1	Left side of the comparison
CONF2	Right side of the comparison

Named Arguments

-o, --output	File where difference is stored. Defaults to standard out.
--comments, -C	Enable comparison of comments. (Unlikely to work consistently)

Example

Add screenshot here

To use `ksconf diff` as an external diff tool, check out *Ksconf as external diff tool*.

3.4.5 `ksconf filter`

Filter the contents of a `conf` file in various ways. Stanzas can be included or excluded based on a provided filter or based on the presence or value of a key.

Where possible, this command supports GREP-like arguments to bring a familiar feel.

```
usage: ksconf filter [-h] [-o FILE] [--comments] [--verbose]
                  [--match {regex,wildcard,string}] [--ignore-case]
                  [--invert-match] [--files-with-matches]
                  [--count | --brief] [--stanza PATTERN]
                  [--attr-present ATTR] [--keep-attrs WC-ATTR]
```

(continues on next page)

(continued from previous page)

```
[--reject-attrs WC-ATTR]
CONF [CONF ...]
```

Positional Arguments

CONF Input conf file

Named Arguments

-o, --output File where the filtered results are written. Defaults to standard out.

--comments, -C Preserve comments. Comments are discarded by default.

--verbose Enable additional output.

--match, -m Possible choices: regex, wildcard, string

 Specify pattern matching mode. Defaults to 'wildcard' allowing for * and ? matching. Use 'regex' for more power but watch out for shell escaping. Use 'string' to enable literal matching.

--ignore-case, -i Ignore case when comparing or matching strings. By default matches are case-sensitive.

--invert-match, -v Invert match results. This can be used to show what content does NOT match, or make a backup copy of excluded content.

Output mode

Select an alternate output mode. If any of the following options are used, the stanza output is not shown.

--files-with-matches, -l List files that match the given search criteria

--count, -c Count matching stanzas

--brief, -b List name of matching stanzas

Stanza selection

Include or exclude entire stanzas using these filter options.

All filter options can be provided multiple times. If you have a long list of filters, they can be saved in a file and referenced using the special `file://` prefix. One entry per line.

--stanza Match any stanza who's name matches the given pattern. PATTERN supports bulk patterns via the `file://` prefix.

--attr-present Match any stanza that includes the ATTR attribute. ATTR supports bulk attribute patterns via the `file://` prefix.

Attribute selection

Include or exclude attributes passed through. By default, all attributes are preserved. Allowlist (keep) operations are preformed before blacklist (reject) operations.

- keep-attrs** Select which attribute(s) will be preserved. This space separated list of attributes indicates what to preserve. Supports wildcards.
- reject-attrs** Select which attribute(s) will be discarded. This space separated list of attributes indicates what to discard. Supports wildcards.

How is this different than btool?

Some of the things filter can do functionally overlaps with **btool list**. Take for example:

```
ksconf filter search/default/savedsearches.conf --stanza "Messages by minute last 3 hours"
```

Is essentially the same as:

```
splunk btool --app=search savedsearches list "Messages by minute last 3 hours"
```

The output is the same, assuming that you didn't overwrite any part of that search in local. But if you take off the `--app` argument, you'll quickly see that `btool` is merging all the layers together to show the final value of all attributes. That is certainly a helpful thing to do, but not always what you want.

`Ksconf` is *only* going to look at the file you explicitly pointed it to. It doesn't traverse the tree on it's own. This means that it works on app directory structure that live inside or outside of your Splunk instance. If you've ever tried to run `btool check` on an app that you haven't installed yet, then you'll understand the value of this.

In many other cases, the usage of both `ksconf filter` and `btool` differ significantly.

Examples

Lift and shift

Copy all indexes defined within a specific app.

```
cd $SPLUNK_DB
for idx in $(ksconf filter $SPLUNK_HOME/etc/app/MyApp/default/indexes.conf --brief)
do
  echo "Copy index ${idx}"
  tar -czf "/migrate/export-${idx}" "${idx}"
done
```

Now you'll have a copy all of the necessary indexes in the `/migrate` folder to make `MyApp` work on another Splunk instance. Of course, there's likely other migration tasks to consider, like copying the actual app. This is just one way `ksconf` can help.

Can I do the same thing with standard unix tools?

Sure, go for it!

Yes, there's significant overlap with the filter command and what you can do with **grep**, **awk**, or **sed**. Much of that is on purpose, and in fact some command line arguments were borrowed.

I used to do these tasks by hand, but it's easy to make mistakes. The idea of **ksconf** is to give you stable and reliable tools that are more suitable for `.conf` file work. Also keep in mind that these features are expanding much more quickly than the unix tools change.

Although, if you've had to deal with BSD vs GNU tools and trying to find a set of common arguments, then you probably already appreciate how awesome a domain-specific-tool like this is.

3.4.6 ksconf merge

Merge two or more `.conf` files into a single combined `.conf` file. This is similar to the way that Splunk logically combines the `default` and `local` folders at runtime.

```
usage: ksconf merge [-h] [--target FILE] [--ignore-missing] [--dry-run]
                  [--banner BANNER]
                  FILE [FILE ...]
```

Positional Arguments

FILE The source configuration file(s) to collect settings from.

Named Arguments

--target, -t Save the merged configuration files to this target file. If not provided, the merged conf is written to standard output.

--ignore-missing, -s Silently ignore any missing CONF files.

--dry-run, -D Enable dry-run mode. Instead of writing to TARGET, preview changes in 'diff' format. If TARGET doesn't exist, then show the merged file.

--banner, -b A banner or warning comment added to the top of the TARGET file. Used to discourage Splunk admins from editing an auto-generated file.

Examples

Here is an elementary example that merges all `props.conf` file from *all* of your technology addons into a single output file:


```
ksconf merge --target=all-ta-props.conf etc/apps/*TA*/{default,local}/props.conf
```

See an expanded version of this example here: [Building an all-in one TA for your indexing tier](#)

3.4.7 ksconf minimize

See also:

See the [Minimizing files](#) for background on why this is important.

Minimize a conf file by removing any duplicated default settings.

Reduce a local conf file to only your intended changes without manually tracking which entries you've edited. Minimizing local conf files makes your local customizations easier to read and often results in cleaner upgrades.

```
usage: ksconf minimize [-h] [--target TARGET] [--dry-run | --output OUTPUT]
                        [--explode-default] [-k PRESERVE_KEY]
                        CONF [CONF ...]
```

Positional Arguments

CONF The default configuration file(s) used to determine what base settings are. The base settings determine what is unnecessary to repeat in target file.

Named Arguments

--target, -t The local file that you wish to remove duplicate settings from. This file will be read from and then replaced with a minimized version.

--dry-run, -D Enable dry-run mode. Instead of writing and minimizing the TARGET file, preview what would be removed as a 'diff'.

--output Write the minimized output to a separate file instead of updating TARGET.

This option can be used to *preview* the actual changes. Sometimes if `--dry-run` mode produces too much output, it's helpful to look at the actual minimized version of the file in concrete form (rather than a relative format, like a diff.) This may also be helpful in other workflows.

--explode-default, -E Enable minimization across stanzas for special use-cases. Helpful when dealing with stanzas downloaded from a REST endpoint or `btool list` output.

This mode will not only minimize the same stanza across multiple config files, it will also attempt to minimize any default values stored

in the [default] or global stanza as well. For this to be effective, it's often necessary to include system-level defaults in the CONF list. For example, to trim out cruft in savedsearches.conf, make sure you add etc/system/default/savedsearches.conf as an input.

-k, --preserve-key Specify attributes that should always be kept.

Example usage

```
cd Splunk_TA_nix
cp default/inputs.conf local/inputs.conf

# Edit 'disabled' and 'interval' settings in-place
vi local/inputs.conf

# Remove all the extra (unmodified) bits
ksconf minimize --target=local/inputs.conf default/inputs.conf
```

Undoing a minimize

You can use *ksconf merge* to reverse the effect of minimize by running a command like so:

```
ksconf merge default/inputs.conf local/inputs.conf
```

Additional capabilities

For special cases, the `--explode-default` mode reduces duplication between entries in normal stanzas (as normal) and then additionally reduces duplication between individual stanzas and default entries. Typically you only need this mode if your dealing with a conf file that's been fully expanded to include all the layers, which doesn't happen under normal circumstances. This does happen anytime you download a stanza from a REST endpoint or munge together output from `btool list`. If you've ever done this with `savedsearches.conf` stanzas, you'll be painfully aware of how massive they are! This is the exact use case that `--explode-default` was written for.

In such a case, it may be helpful to minimize against the full definition of *default*, which effectively requires looking at all the layers of default. This includes all global app settings, and system-level settings.

There are limitations to this approach.

- You have to manually list out all the layers. (Sometimes just pointing to the system-level defaults is good enough)
- Minimize doesn't take namespace into account. This means ownership, sharing, and ACLs are ignored.

In many ways minimize mimics what Splunk does *every* time it updates a conf file, as discussed in *How Splunk writes to conf files*. If you find yourself frequently needing the power of

`--explode-default`, at some point a potentially better approach may be to simply post stanzas to the REST endpoint. However, this typically does a good enough job, especially for offline scenarios.

Additionally, this command doesn't strictly require a bloated file. For example, if `disabled = 0` is both a global default, and set on a per-stanza basis, that could be reduced too. However, typically this isn't super helpful.

3.4.8 kscnf package

Create a Splunk app or add on tarball (.spl) file from an app directory.

`kscnf package` can do useful things like, exclude unwanted files, combine layers, set the application version and build number, drop or promote the local directory into default.

```
usage: kscnf package [-h] [-f SPL] [--app-name APP_NAME]
                  [--blocklist BLOCKLIST] [--allowlist ALLOWLIST]
                  [-I PATTERN] [-E PATTERN] [--follow-symlink]
                  [--set-version VERSION] [--set-build BUILD]
                  [--allow-local | --block-local | --merge-local]
                  [--release-file RELEASE_FILE] [--hook-script COMMAND]
SOURCE
```

Positional Arguments

SOURCE Source directory for the Splunk app.

Named Arguments

-f, --file Name of splunk app file (tarball) to create.

--app-name Specify the top-level app folder name. If this is not given, the app folder name is automatically extracted from the basename of SOURCE.

--blocklist, -b Pattern for files/directories to exclude. Can be given multiple times. You can load multiple exclusions from disk by using `file://path` which can be used with `.gitignore` for example. (Default includes: `.git*`, `*.py[co]`, `__pycache__`, `.DS_Store`)

--allowlist, -w Remove a pattern that was previously added to the blocklist.

--follow-symlink, -l Follow symbolic links pointing to directories. Symlinks to files are always followed.

--set-version Set application version. By default the application version is read from `default/app.conf`

--set-build Set application build number.

- allow-local** Allow the local folder to be kept. **WARNING:** This goes against Splunk packaging practices, and will cause AppInspect to fail. However, this option can be useful for private package transfers between servers or possibly for app backups.
- block-local** Block the local folder and local.meta from the resulting SPL.
- merge-local** Merge any files in local into the default folder when build the archive. This is the default behavior.

Layer filtering

If the app being packaged includes multiple layers, these arguments can be used to control which ones should be included in the final app file. If no layer options are specified, then all layers will be included.

- I, --include** Name or pattern of layers to include.
- E, --exclude** Name or pattern of layers to exclude from the target.

Advanced Build Options

The following options are for more advanced app building workflows.

- release-file** Write the path of the newly generated archive file (SPL) after the archive is written. This is useful in build scripts when the SPL contains variables so the final name may not be known ahead of time.
- hook-script** Run the given command or script. This is run after all layer have been combined, and local directory handling, but before blocklist cleanup. Therefore if this command produces any unwanted files they can be removed with a `--blocklist` entry. This can be used to install python packages, for example.

Example

```
ksconf package -f my_app.tgz MyApp
```

3.4.9 ksconf promote

Propagate `.conf` settings applied in one file to another. Typically this is used to move local changes (made via the UI) into another layer, such as the `default` or a named `default.d/50-xxxxx` folder.

Promote has two modes: batch and interactive. In batch mode, all changes are applied automatically and the (now empty) source file is removed. In interactive mode, the user is prompted to select stanzas to promote. This way local changes can be held without being promoted.

NOTE: Changes are *MOVED* not copied, unless `--keep` is used.

```
usage: ksconf promote [-h] [--batch | --interactive | --summary] [--verbose]
                    [--match {regex,wildcard,string}] [--ignore-case]
                    [--invert-match] [--stanza PATTERN] [--force] [--keep]
                    [--keep-empty]
                    SOURCE TARGET
```

Positional Arguments

SOURCE	The source configuration file to pull changes from. (Typically the local conf file)
TARGET	Configuration file or directory to push the changes into. (Typically the default folder)

Named Arguments

--batch, -b	Use batch mode where all configuration settings are automatically promoted. All changes are removed from source and applied to target. The source file will be removed unless <code>--keep-empty</code> is used.
--interactive, -i	Enable interactive mode where the user will be prompted to approve the promotion of specific stanzas and attributes. The user will be able to apply, skip, or edit the changes being promoted.
--summary, -s	Summarize content that could be promoted.
--verbose	Enable additional output.
--force, -f	Disable safety checks. Don't check to see if SOURCE and TARGET share the same basename.
--keep, -k	Keep conf settings in the source file. All changes will be copied into the TARGET file instead of being moved there. This is typically a bad idea since local always overrides default.
--keep-empty	Keep the source file, even if after the settings promotions the file has no content. By default, SOURCE will be removed after all content has been moved into TARGET. Splunk will re-create any necessary local files on the fly.

Automatic filtering options

Include or exclude stanzas to promote using these filter options. Stanzas selected by these filters will be promoted.

All filter options can be provided multiple times. If you have a long list of filters, they can be saved in a file and referenced using the special `file://` prefix. One entry per line.

- match, -m** Possible choices: regex, wildcard, string
Specify pattern matching mode. Defaults to 'wildcard' allowing for * and ? matching. Use 'regex' for more power but watch out for shell escaping. Use 'string' to enable literal matching.
- ignore-case** Ignore case when comparing or matching strings. By default matches are case-sensitive.
- invert-match, -v** Invert match results. This can be used to prevent content from being promoted.
- stanza** Promote any stanza with a name matching the given pattern. PATTERN supports bulk patterns via the file:// prefix.

Warning: The promote command **moves** configuration settings between *SOURCE* and *TARGET* and therefore both files are updated. This is unlike most other commands where only *TARGET* is modified. Using the `--keep` argument will prevent *SOURCE* from being updated.

Modes

Promote has different modes:

Batch mode Changes are applied automatically and the (now empty) source file is removed by default. The source file can be retained by using either the `--keep` or `--keep-empty` arguments, see descriptions above.

Interactive mode Prompts the user to pick which stanzas and attributes to integrate. In practice, it's common that not all local changes will be ready to be promoted and committed at the same time.

Hint: This mode was inspired by `git add --patch` command.

Summary mode Shows the user a brief breakdown of what stanzas are available for promotion. This can be used to simplify the use of the `--stanza` filtering options (automatic promotion) to show the names of stanzas available for promotion. Note that when `--summary` and `--stanza` are used at the same time, then the summary output will include any output not *already* matched by `--stanza` filter.

Default If you haven't specified either batch or interactive mode, you'll be asked to pick one at startup. You'll be given the option to show a diff, apply all changes, or be prompted to keep or reject changes interactively.

Automated promotions

Ksconf 0.7.8 added support for automatic stanza matching and promotion using a `ksconf` filter-like CLI options.

Key features include:

Automatic promotion of stanzas One or more named stanzas can be promoted automatically using the `--stanza` argument. This argument can be given multiple times to match multiple stanzas at once. In batch mode, only the named stanzas will be promoted; but in interactive mode, the named stanzas will be promoted first, and any content remaining to be promoted can be handled interactively.

Matching mode Like with the `ksconf filter` command, multiple methods of matching are supported. This includes: string matching (default), wildcard (or “glob”) matching, and regular expressions.

Inversion The `--invert-match` option allows for the selection to be inverted. In this mode, it’s possible to select which stanzas should *not* be promoted. This can be used as a blacklist to prevent accidental promotions.

Safety checks

Moving content between files is a potentially risky operation. Here are some of the safety mechanisms that `ksconf` has in place to prevent data loss.

Tip: Pairing `ksconf` with a version control tool like `git`, while not required, does provide another layer of protection against loss or corruption. If you promote and commit changes frequently, then the scope of potential loss is reduced.

Syntax checking Strong syntax checking is enabled for both *SOURCE* and *TARGET* to prevent mistakes, such as dangling or duplicate stanzas, which could lead to even more corruption.

File fingerprinting Various attributes of the *SOURCE* and *TARGET* files are captured at startup and compared again before any changes are written to disk. This reduces the possibility of a race-condition on a live Splunk system. This mostly impacts interactive mode because the session lasts longer. If this is a concern, run `promote` only when Splunk is offline.

Same file check Attempts to promote content from a file to itself are prevented. While logically no one would want to do this, in practice having a clear error message saves time and confusion.

Base name check The *SOURCE* and *TARGET* should share the same base name. In other words, trying to promote from `inputs.conf` into `props.conf` (due to a typo) will be prevented. This matters more in batch mode. In interactive mode, it should be pretty obvious that the type of entries don’t make sense and therefore the user can simply exit without saving.

For scripting purposes, there may be times where pushing changes between arbitrary-named files is helpful, so this check can be bypassed by using the `--force` argument.

Note: Unfortunately, the unit testing coverage for the promote command is quite low. This is primarily because I haven't yet figured out how to handle unit testing for interactive CLI tools (as this is the only interactive command to date.) I'm also not sure how much the UI may change; Any assistance in this area would be greatly appreciated.

Examples

A simple promotion looks like this.

```
ksconf promote local/props.conf default/props.conf
```

This is equivalent to this minor shortcut.

```
ksconf promote local/props.conf default
```

In this case, ksconf determines that default is a directory and therefore assumes that you want the same filename, props.conf in this case.

Tip: Using a directory as TARGET may seem like a trivial improvement, but in practice it greatly reduces accidental cross-promotion of content. Therefore, we suggest its use.

Similarly, a shortcut for pushing between metadata files exists:

```
ksconf promote metadata/local.meta metadata
```

A few example of automatic promotion of a named stanza:

```
# Single stanzas
ksconf promote local/savedsearches.conf default --stanza "My fancy search"

# Wildcard promote all prod server alerts
ksconf promote local/savedsearches.conf default --match wildcard --stanza "Server_
↳PRD* Alert"

# Automatically promote everything except for one search:
ksconf promote local/savedsearches.conf default --batch --invert-match --stanza
↳"Local test"
```

Interactive mode

Keyboard shortcuts

Key	Meaning	Description
y	Yes	Apply changes
n	No	Don't apply
d	Diff	Show the difference between the file or stanza.
q	Quit	Exit program. Don't save changes.

Limitations

- Currently, an attribute-level section has not been implemented. Entire stanzas are either kept local or promoted fully.
- Interactive mode currently lacks “help”. In the meantime, see the keyboard shortcuts listed above.
- At present, comments in the *SOURCE* file will not be preserved.
- If *SOURCE* or *TARGET* is modified externally while promote is running, the entire operation will be aborted, thus losing any custom selections you made in interactive mode. This needs improvement.
- There's currently no way to preserve certain local settings with some kind of “never-promote” flag. It's not uncommon to have some settings in *inputs.conf*, for example, that you never want to promote.
- There is no *dry-run* mode supported. Primarily, this is because it would only work for batch mode, and in interactive mode you explicitly see exactly what will be changed before anything is applied. (If you really need a dry-run for batch mode, use *ksconf merge* to show the result of *TARGET SOURCE* combined.)

3.4.10 ksconf rest-export

Deprecated since version 0.7.0: You should consider using *ksconf rest-publish* instead of this one. The only remaining valid use case for *rest-export* (this command) is for disconnected scenarios. In other words, if you need to push stanzas to a Splunkd instance where you don't (and can't) install *ksconf*, then this command may still be useful to you. In this case, *ksconf rest-export* can create a shell script that you can transfer to the correct network, and then run the shell script. But for **ALL** other use cases, the *rest-publish* command is superior.

Build an executable script of the stanzas in a configuration file that can be later applied to a running Splunk instance via the Splunkd REST endpoint.

This can be helpful when pushing complex props and transforms to an instance where you only have UI access and can't directly publish an app.

```
usage: ksconf rest-export [-h] [--output FILE] [--disable-auth-output]
                        [--pretty-print] [-u | -D] [--url URL] [--app APP]
                        [--user USER] [--owner OWNER] [--conf TYPE]
                        [--extra-args EXTRA_ARGS]
                        CONF [CONF ...]
```

Positional Arguments

CONF Configuration file(s) to export settings from.

Named Arguments

--output, -t Save the shell script output to this file. If not provided, the output is written to standard output.

-u, --update Assume that the REST entities already exist. By default, output assumes stanzas are being created.

-D, --delete Remove existing REST entities. This is a destructive operation. In this mode, stanza attributes are unnecessary and ignored. NOTE: This works for 'local' entities only; the default folder cannot be updated.

--url URL of Splunkd. Default: "https://localhost:8089"

--app Set the namespace (app name) for the endpoint

--user Deprecated. Use `--owner` instead.

--owner Set the object owner. Typically, the default of 'nobody' is ideal if you want to share the configurations at the app-level.

--conf Explicitly set the configuration file type. By default, this is derived from CONF, but sometimes it's helpful to set this explicitly. Can be any valid Splunk conf file type. Examples include: 'app', 'props', 'tags', 'savedsearches', etc.

--extra-args Extra arguments to pass to all CURL commands. Quote arguments on the command line to prevent confusion between arguments to `ksconf` vs `curl`.

Output Control

--disable-auth-output Turn off sample login curl commands from the output.

--pretty-print, -p Enable pretty-printing. Make shell output a bit more readable by splitting entries across lines.

Warning: For interactive use only!

This command is indented for manual admin workflows. It's quite possible that shell escaping bugs exist that may allow full shell access if you put this into an automated workflow. Evaluate the risks, review the code, run as a least-privilege user, and be responsible.

Roadmap

For now, the assumption is that `curl` command will be used. (Patches to support the Power Shell `Invoke-WebRequest` cmdlet would be greatly welcomed!)

Example

```
ksconf rest-export --output=apply_props.sh etc/app/Splunk_TA_aws/local/props.conf
```

3.4.11 ksconf rest-publish

Note: This command effectively replaces *ksconf rest-export* for nearly all use cases. The only thing that `rest-publish` can't do that `rest-export` can, is handle a disconnected scenario. But for **ALL** other use cases, the `rest-publish` (this command) command is far superior.

Note: This commands requires the Splunk Python SDK, which is automatically bundled with the *Splunk app for KSCONF*.

Publish stanzas in a `.conf` file to a running Splunk instance via REST. This requires access to the HTTPS endpoint of Splunk. By default, `ksconf` will handle both the creation of new stanzas and the update of existing stanzas.

This can be used to push full configuration stanzas where you only have REST access and can't directly publish an app.

Only attributes present in the `conf` file are pushed. While this may seem obvious, this fact can have profound implications in certain situations, like when using this command for continuous updates. This means that it's possible for the source `.conf` to ultimately differ from what ends up on the server's `.conf` file. One way to avoid this, is to explicitly remove an object using `--delete` mode first, and then insert a new copy of the object. Of course, this means that the object will be unavailable. The other impact is that `diffs` only compares and shows a subset of attribute.

Be aware, that for consistency, the `configs/conf-TYPE` endpoint is used for this command. Therefore, a reload may be required for the server to use the published config settings.

```
usage: ksconf rest-publish [-h] [--conf TYPE] [-m META] [--url URL]
                          [--user USER] [--pass PASSWORD] [-k]
                          [--session-key SESSION_KEY] [--app APP]
                          [--owner OWNER] [--sharing {user,app,global}] [-D]
                          CONF [CONF ...]
```

Positional Arguments

CONF Configuration file(s) to export settings from.

Named Arguments

--conf	Explicitly set the configuration file type. By default, this is derived from CONF, but sometimes it's helpful to set this explicitly. Can be any valid Splunk conf file type. Examples include: 'app', 'props', 'tags', 'savedsearches', etc.
-m, --meta	Specify one or more .meta files to determine the desired read & write ACLs, owner, and sharing for objects in the CONF file.
--url	URL of Splunkd. Default: "https://localhost:8089"
--user	Login username Splunkd. Default: "admin"
--pass	Login password Splunkd. Default: "changeme"
-k, --insecure	Disable SSL cert validation.
--session-key	Use an existing session token instead of using a username and password to login.
--app	Set the namespace (app name) for the endpoint
--owner	Set the user who owns the content. The default of 'nobody' works well for app-level sharing.
--sharing	Possible choices: user, app, global Set the sharing mode.
-D, --delete	Remove existing REST entities. This is a destructive operation. In this mode, stanza attributes are unnecessary. NOTE: This works for 'local' entities only; the default folder cannot be updated.

Examples

A simple example:

```
ksconf rest-publish etc/app/Splunk_TA_aws/local/props.conf \  
  --user admin --password secret --app Splunk_TA_aws --owner nobody --sharing global
```

This command also supports replaying metadata like ACLs:

```
ksconf rest-publish etc/app/Splunk_TA_aws/local/props.conf \  
  --meta etc/app/Splunk_TA_aws/metdata/local.meta \  
  --user admin --password secret --app Splunk_TA_aws
```

3.4.12 ksconf snapshot

Build a static snapshot of various configuration files stored within a structured json export format. If the .conf files being captured are within a standard Splunk directory structure, then certain

metadata and namespace information is assumed based on typical path locations. Individual apps or conf files can be collected as well, but less metadata may be extracted.

```
usage: kscnf snapshot [-h] [--output FILE] [--minimize] PATH [PATH ...]
```

Positional Arguments

PATH Directory from which to load configuration files. All .conf and .meta file are included recursively.

Named Arguments

--output, -o Save the snapshot to the named files. If not provided, the snapshot is written to standard output.

--minimize Reduce the size of the JSON output by removing whitespace. Reduces readability.

Warning: Output NOT stable!

The output from this command hasn't really been tested in any kind of serious way for usability. Consider this a proof-of-concept. Anyone interested in this type of functionality should *reach out* to discuss uses cases.

Example

```
kscnf snapshot --output=daily-$(date +%Y-%m-%d).json $SPLUNK_HOME/etc/app/
```

3.4.13 kscnf sort

Sort a Splunk .conf file. Sort has two modes: (1) by default, the sorted config file will be echoed to the screen. (2) the config files are updated in-place when the `-i` option is used.

Manually managed conf files can be protected against changes by adding a comment containing the string `KSCONF-NO-SORT` to the top of any .conf file.

```
usage: kscnf sort [-h] [--target FILE | --inplace] [-F] [-q] [-n LINES]
                FILE [FILE ...]
```

Positional Arguments

FILE Input file to sort, or standard input.

Named Arguments

- target, -t** File to write results to. Defaults to standard output.
- inplace, -i** Replace the input file with a sorted version.
WARNING: This a potentially destructive operation that may move/remove comments.
- n, --newlines** Number of lines between stanzas.

In-place update arguments

- F, --force** Force file sorting for all files, even for files containing the special 'KSCONF-NO-SORT' marker.
- q, --quiet** Reduce the output. Reports only updated or invalid files. This is useful for pre-commit hooks, for example.

See also:

Pre-commit hooks

See *Pre-commit hooks* for more information about how the sort command can be easily integrated in your git workflow.

Examples

To recursively sort all files

```
find . -name '*.conf' | xargs kscnf sort -i
```

3.4.14 kscnf unarchive

Install or overwrite an existing app in a git-friendly way. If the app already exists, steps will be taken to upgrade it safely.

The default folder can be redirected to another path (i.e., default.d/10-upstream or other desirable path if you're using the kscnf combine tool to manage extra layers).

```
usage: kscnf unarchive [-h] [--dest DIR] [--app-name NAME]
                      [--default-dir DIR] [--exclude EXCLUDE] [--keep KEEP]
                      [--allow-local]
                      [--git-sanity-check {off,changed,untracked,ignored}]
                      [--git-mode {nochange,stage,commit}] [--no-edit]
                      [--git-commit-args GIT_COMMIT_ARGS]
                      SPL
```

Positional Arguments

SPL The path to the archive to install.
Supports tarballs (.tar.gz, .spl), and less-common zip files (.zip)

Named Arguments

--dest Set the destination path where the archive will be extracted. By default, the current directory is used. Sane values include: etc/apps, etc/deployment-apps, and so on.

Often this will be a git repository working tree where Splunk apps are stored.

--app-name The app name to use when expanding the archive. By default, the app name is taken from the archive as the top-level path included in the archive (by convention).

Expanding archives that contain multiple (ITSI) or nested apps (NIX, ES) is not supported.

--default-dir Name of the directory where the default contents will be stored. This is a useful feature for apps that use a dynamic default directory that's created and managed by the 'combine' mode.

--exclude, -e Add a file pattern to exclude from extraction. Splunk's pseudo-glob patterns are supported here. * for any non-directory match, ... for ANY (including directories), and ? for a single character.

--keep, -k Specify a pattern for files to preserve during an upgrade. Repeat this argument to keep multiple patterns.

--allow-local Allow local/* and local.meta files to be extracted from the archive.

Shipping local files is a Splunk app packaging violation so local files are blocked to prevent customizations from being overridden.

--git-sanity-check By default, git status is run on the destination folder to detect working tree or index modifications before the unarchive process starts, but this is configurable. Sanity check choices go from least restrictive to most thorough:

- Use off to prevent any 'git status' safety checks.
- Use changed to abort only upon local modifications to files tracked by git.
- Use untracked (the default) to look for changed and untracked files before considering the tree clean.
- Use ignored to enable the most intense safety check which will abort if local changes, untracked, or ignored files are found.

- git-mode** Possible choices: nochange, stage, commit
- Set the desired level of git integration. The default mode is *stage*, where new, updated, or removed files are automatically handled for you.
- To prevent any `git add` or `git rm` commands from being run, pick the ‘nochange’ mode.
- If a `git commit` is incorrect, simply roll it back with `git reset` or fix it with a `git commit --amend` before the changes are pushed anywhere else. There’s no native `--dry-run` or `undo` for unarchive mode because that’s why you’re using git in the first place, right? (Plus, such features would require significant overhead and unit testing.)
- no-edit** Tell git to skip opening your editor on commit. By default, you will be prompted to review/edit the commit message. (Git Tip: Delete the content of the default message to abort the commit.)
- git-commit-args, -G** Extra arguments to pass to ‘git’

Note: What if I’m not using version control?

Sanity checks and commit modes are automatically disabled if the app is being installed into a directory that is *not* contained within a git working tree. Ksconf confirms that *git* is present and functional before running sanity checks.

3.4.15 ksconf xml-format

Normalize and apply consistent XML indentation and CDATA usage for XML dashboards and navigation files.

Technically this could be used on *any* XML file, but certain element names specific to Splunk’s simple XML dashboards are handled specially, and therefore could result in unusable results.

The expected indentation level is guessed based on the first element indentation, but can be explicitly set if not detectable.

```
usage: ksconf xml-format [-h] [--indent INDENT] [--quiet] FILE [FILE ...]
```

Positional Arguments

- FILE** One or more XML files to check. If ‘-’ is given, then a list of files is read from standard input

Named Arguments

--indent	Number of spaces. This is only used if indentation cannot be guessed from the existing file.
--quiet, -q	Reduce the volume of output.

See also:

Pre-commit hooks

See [Pre-commit hooks](#) for more information about how the `xml-format` command can be integrated in your git workflow.

NOTE: While it may work on other XML files, it hasn't been tested for other files, and therefore is not recommended as a general-purpose XML formatter. Specific awareness of various Simple XML tags is baked into this product.

Note: This command requires the external `lxml` Python module.

This package was specifically selected (over the built-in 'xml.etree' interface) because it (1) supports round-trip preservation of CDATA blocks, and (2) already ships with Splunk's embedded Python.

This is an optional requirement, unless you want to use the `xml-format` command. However, due to packaging limitations and pre-commit hook support, installation of the python package will result in an attempt to install `lxml` as well. Please [reach out](#) if this is causing issues for you; I'm looking into other options too.

Why is this important?

TODO: Note the value of using `<!CDATA[[]>` blocks.

Value of consistent indentation.

To recursively format xml files

```
find . -path '*/data/ui/views/*.xml' -o -path '*/data/ui/nav/*.xml' | kscnf xml-format -
```

3.5 Cheat Sheet

Here's a quick rundown of handy `kscnf` commands:

Note: Note that for clarity, most of the command line arguments are given in their long form, but many options also have a short form.

Long commands may be broken across line for readability. When this happens, a trailing backslash (\) is added so the command could still be copied verbatim into most shells.

Contents

- *Cheat Sheet*
 - *General purpose*
 - * *Comparing files*
 - * *Sorting content*
 - * *Extract specific stanza*
 - * *Remove unwanted settings*
 - *Cleaning up*
 - * *Reduce cruft in local*
 - * *Pushing local changes to default*
 - *Packaging and building apps*
 - * *Quick package and install*
 - *Advanced usage*
 - * *Migrating content between apps*
 - * *Migrating the ‘users’ folder*
 - * *Maintaining apps stored in a local git repository*
 - *Putting it all together*
 - * *Pulling out a stanza defined in both default and local*
 - * *Building an all-in one TA for your indexing tier*

3.5.1 General purpose

Comparing files

Show the differences between two conf files using *ksconf diff*.

```
ksconf diff savedsearches.conf savedsearches-mine.conf
```

Sorting content

Create a normalized version of a configuration file, making conf files easier to merge with **git**. Run an in-place sort like so:

```
ksconf sort --inplace savedsearches.conf
```

Tip: Use the `ksconf-sort` *pre-commit* hook to do this for you.

Extract specific stanza

Say you want to *grep* your conf file for a specific stanza pattern:

```
ksconf filter search/default/savedsearches.conf --stanza 'Errors in the last *'
```

Say you want to list stanzas containing `cron_schedule`:

```
ksconf filter Splunk_TA_aws/default/savedsearches.conf --brief \  
--attr-present 'cron_schedule'
```

Remove unwanted settings

Say you want to remove `vsid` from a legacy `savedsearches` file:

```
ksconf filter search/default/savedsearches.conf --reject-attrs "vsid"
```

To see just to the schedule and scheduler status of scheduled searches, run:

```
ksconf filter Splunk_TA_aws/default/savedsearches.conf \  
--attr-present cron_schedule \  
--keep-attrs 'cron*' \  
--keep-attrs enableSched \  
--keep-attrs disabled
```

3.5.2 Cleaning up

Reduce cruft in local

If you're in the habit of copying the *default* files to *local* in the TAs you deploy, here is a quick way to 'minimize' your files. This will reduce the *local* file by removing all the *default* settings you copied but didn't change. (The importance of this is outlined in *Minimizing files*.)

```
ksconf minimize Splunk_TA_nix/default/inputs.conf --target Splunk_TA_nix/local/  
↳inputs.conf
```

Pushing local changes to default

App developers can push changes from the local folder to the default folder:

```
ksconf promote --interactive myapp/local/props.conf myapp/default/props.conf
```

You will be prompted to pick which items you want to promote. Alternatively, use the `--batch` option to promote everything in one step, without reviewing the changes first.

3.5.3 Packaging and building apps

Quick package and install

Use the `--release-file` option of the package command to write out the name of the final created tarball. This helps when the final tarball name isn't known in advance because it contains a version string, for example. By simply placing the latest release in a static location, this allows commonly repeated operations, like `build+install` be chained together in a convenient way making iterations quite fast from a shell.

```
cd my-apps
ksconf package kintyre_app_speedtest --release-file .release && $SPLUNK_HOME/bin/
↪ splunk install app $(<.release) -update 1
```

To save time, I often put this command (along with a first-time install) command in a README or DEVELOPMENT file at the top-level of the app repo.

3.5.4 Advanced usage

Migrating content between apps

Say you want to move a bunch of savedsearches from search into a more appropriate app. First create a file that lists all the names of your searches (one per line) in `corp_searches.txt`. Next, copy just the desired stanzas, those named in the 'corp_searches' file, over to your new corp_app application.

```
ksconf filter --match string --stanza 'file://corp_searches.txt' \
  search/local/savedsearches.conf --output corp_app/default/savedsearches.conf
```

Now, to avoid duplication and confusion, you want to remove that exact same set of searches from the search app.

```
ksconf filter --match string --stanza 'file://corp_searches.txt' \
  --invert-match search/local/savedsearches.conf \
  --output search/local/savedsearches.conf.NEW

# Backup the original
mv search/local/savedsearches.conf \
  /my/backup/location/search-savedsearches-$(date +%Y%M%D).conf
```

(continues on next page)

(continued from previous page)

```
# Move the updated file in place
mv search/local/savedsearches.conf.NEW search/local/savedsearches.conf
```

Note: Setting the matching mode to string prevents any special characters that may be present in your search names from being interpreted as wildcards.

Migrating the 'users' folder

Say you stood up a new Splunk server and the migration took longer than expected. Now you have two users folders and don't want to lose all the goodies stored in either one. You've copied the users folder to user_old. You're working from the new server and would generally prefer to keep whatever is on the new server over what is on the old. (This is because some of your users copied over some of their critical alerts manually while waiting for the migration to complete, and they've made updates they don't want to lose.)

After stopping Splunk on the new server, run the following commands.

```
mv /some/share/users_old $SPLUNK_HOME/etc/users.old
mv $SPLUNK_HOME/etc/users $SPLUNK_HOME/etc/users.new

ksconf combine $SPLUNK_HOME/etc/users.old $SPLUNK_HOME/etc/users.new \
  --target $SPLUNK_HOME/etc/users --banner ''
```

Now double check the results and start Splunk.

We use the `--banner` option here to essentially disable an output banner. Because, in this case, the combine operation is a one-time job and therefore no warning is needed.

Maintaining apps stored in a local git repository

```
ksconf unarchive
```

3.5.5 Putting it all together

Pulling out a stanza defined in both default and local

Say you wanted to count the number of searches containing the word error

```
ksconf merge default/savedsearches.conf local/savedsearches.conf \
  | ksconf filter - --stanza '*Error*' --ignore-case --count
```

This is a simple example of chaining two basic `ksconf` commands together to perform a more complex operation. The first command handles the merge of default and local `savedsearches.conf` into a single output stream. The second command filters the resulting stream finding stanzas containing the word 'Error'.

Building an all-in one TA for your indexing tier

Say you need to build a single TA containing all the index-time settings for your indexing tier. (Note: Enterprise Security does something similar when generating the indexer app.)

```
ksconf merge etc/apps/*TA*/{default,local}/props.conf \
| ksconf filter --output=TA-for-indexers/default/props.conf \
  --include-attr 'TRANSFORMS*' \
  --include-attr 'TIME_*' \
  --include-attr 'MUST_BREAK*' \
  --include-attr 'SHOULD_LINEMERGE' \
  --include-attr 'EVENT_BREAKER*' \
  --include-attr 'LINE_BREAKER*'
```

This example is incomplete because it doesn't list *every* index-time `props.conf` attribute, and leaves out `transforms.conf` and `fields.conf`, but hopefully you get the idea.

3.6 Contributing

Pull requests are greatly welcome! If you plan on contributing code back to the main `ksconf` repo, please follow the standard GitHub fork and pull-request work-flow. We also ask that you enable a set of git hooks to help safeguard against avoidable issues.

3.6.1 Pre-commit hook

The `ksconf` project uses the [pre-commit](#) hook to enable the following checks:

- Fixes trailing whitespace, EOF, and EOLs
- Confirms python code compiles (AST)
- Blocks the committing of large files and keys
- Rebuilds the dynamic portions of the docs related to the CLI.
- Confirms that all unit tests pass. (Currently, this is the same test run by Travis CI, but since tests complete in under 5 seconds, the run-everywhere approach seems appropriate for now. Eventually, the local testing will likely become a subset of the full test suite.)

Note: Multiple uses of pre-commit

Be aware, that the [ksconf repo](#) both uses pre-commit for validation of it's own content, and it provides a pre-commit hook service definition for other repos. The first scenario is discussed in this section of the guide. The second scenario is for repositories that house Splunk apps to use `ksconf`

check and *ksconf sort* as easy to use hooks against their own `.conf` files which is discussed further in *Pre-commit hooks*.

Installing the pre-commit hook

To ensure your changes comply with the ksconf coding standards, please install and activate `pre-commit`.

Install:

```
sudo pip install pre-commit

# Register the pre-commit hooks (one time setup)
cd ksconf
pre-commit install --install-hooks
```

Install gitlint

`Gitlint` will check to ensure that commit messages are in compliance with the standard subject, empty-line, and body format. You can enable it with:

```
gitlint install-hook
```

3.6.2 Refresh module listing

After making changes to the module hierarchy or simply adding new commands, refresh the listing for the autodoc extension by running the following command. Note that this may not remove old packages.

```
sphinx-apidoc -o docs/source/ ksconf --force
```

3.6.3 Create a new subcommand

Checklist:

1. Create a new module in `ksconf.commands.<CMD>`.
 - Create a new class derived from `KsconfCmd`. You must, at a minimum, define the following methods:
 - `register_args()` to setup any config parser inputs.
 - `run()` which handles the actual execution of the command.
2. Register a new entrypoint configuration in the `setup_entrypoints.py` script. Edit the `_entry_points` dictionary to add an entry for the new command.
 - Each entry must include command name, module, and implementation class.

3. Create unit tests in `test/test_cli_<CMD>.py`.
4. Create documentation in `docs/source/cmd_<CMD>.rst`. You'll want to build the docs locally to make sure everything looks correct. Part of the documentation is automatically generated from the `argparse` arguments defined in the `register_args()` method, but other bits need to be spelled out explicitly.

When in doubt, it may be helpful to look back over history in git for other recently added commands and use that as an example.

Here's an overview of paths you should expect to update:

File path	Description / purpose
<code>ksconf/commands/fancy.py</code>	The core python code and CLI interface
<code>tests/tests/test_cli_CMD.py</code>	Add new unit test here
<code>docs/source/cmd_CMD.rst</code>	Command line documentation. Make sure to include the <i>argparse</i> module
<code>ksconf/setup_entrypoints.py</code>	Add a new entrypoint line here, or the new command won't be registered
<code>.pre-commit-hooks.yaml</code>	Only needed if the new command is a command is pre-commit hook
<code>setup.py</code>	Update if there are any new external dependancies
<code>requirements.txt</code>	Same as above
<code>make_splunk_app</code>	If there's new dependencies that need to go into the Splunk app

3.6.4 Cookiecutter options

The following example assume we're make a new command called `asciiart`:

```
git clone https://github.com/Kintyre/ksconf.git
cd ksconf

# Kick off a cookiecutter (prompt submodule: asciiart)
cookiecutter https://github.com/Kintyre/ksconf.git -c cookiecutter-subcommand

cp ksconf-asciiart/* .

git add ksconf/commands/*.py docs/source/cmd/*.rst tests/test_cli*.py

# Merge that one line into entrypoints
vim ksconf/setup_entrypoints*.py
git add kconf/setup_entrypoints.py

# Now run-precommit to ensure that the new command is found sucessfully and is importable
```

(continues on next page)

(continued from previous page)

```
pre-commit
# Now go write code, tests, docs and commit ...
```

3.7 Developer setup

The following steps highlight the developer install process.

3.7.1 Tools

If you are a developer, then we strongly suggest installing into a virtual environment to prevent overwriting the production version of ksconf and for the installation of the developer tools. (The virtualenv name ksconfdev-pyve is used below, but this can be whatever suites, just make sure not to commit it.)

```
# Setup and activate virtual environment
virtualenv ksconfdev-pyve
. ksconfdev-pyve/bin/activate

# Install developer packages
pip install -r requirements-dev.txt
```

3.7.2 Install ksconf

```
git clone https://github.com/Kintyre/ksconf.git
cd ksconf
pip install .
```

3.7.3 Building the docs

```
cd ksconf
. ksconfdev-pyve/bin/activate

cd docs
make html
open build/html/index.html
```

If you are actively editing the docs, and would like changes to be updated in your browser as you save changes `.rst` files, then use the script in the root directory:

```
./make_docs
```

If you'd like to build PDF, then you'll need some extra tools. On Mac, you may also want to install the following (for building docs, etc.):

```
brew install homebrew/cask/mactex-no-gui
```

3.7.4 Running TOX

Local testing across multiple versions of python can be accomplished with `tox` and `pyenv`. See the online docs for these tools for more details.

Tox and pyenv can be run like so:

```
# Install the necessary python versions
pyenv install 2.7.17
...
pyenv install 3.8.1

# Set specific default version of python for each major/minor release (tab completion is_
↪your friend here)
pyenv local 2.7.17 ... 3.8.1

# Run tox for ALL python versions
tox

# Run tox for just a specific python version
tox -e py38
```

Some additional information about how to setup and run these tests can be gleaned from the Vagrantfile and Dockerfile in the root of the git repository, though specific python versions contained there may be quite out of date.

3.8 Git tips & tricks

3.8.1 Pre-commit hooks

Ksconf is setup to work as a `pre-commit` plugin. To use ksconf in this manner, simply configure the ksconf repo in your pre-commit configuration file. If you haven't done any of this before, it's not difficult to setup but is beyond the scope of this guide. We suggest that you read the pre-commit docs and review this section when you are ready to setup the hooks.

Hooks provided by ksconf

Three hooks are currently defined by the ksconf repository:

ksconf-check Runs *ksconf check* to perform basic validation tests against all files in your repo that end with `.conf` or `.meta`. Any errors will be reported by the UI at commit time and you'll be able to correct mistakes before bogus files are committed into your repo. If you're not sure why you'd need this, check out *Why validate my conf files?*

ksconf-sort Runs *ksconf sort* to normalize any of your `.conf` or `.meta` files which will make diffs more readable and merging more predictable. As with any hook, you can customize the filename pattern of which files this applies to. For example, to manually organize `props.conf` files, simply add the `exclude` setting. *See Example below.*

ksconf-xml-format: Runs *ksconf xml-format* to apply consistency to your XML representations of Simple XML dashboards and navigation files. Formatting includes appropriate indentation and the automatic addition of `<![CDATA[...]>` blocks, as needed, to reduce the need for XML escaping, resulting in more readable source file. By default, this hook looks at standard locations where XML views and navigation typically live. So if you use Advanced XML, proceed with caution, as they share the same path and haven't been tested.

Configuring pre-commit hooks in you repo

To add ksconf pre-commit hooks to your repository, add the following content to your `.pre-commit-config.yaml` file:

```
repos:
- repo: https://github.com/Kintyre/ksconf
  rev: v0.7.7
  hooks:
  - id: ksconf-check
  - id: ksconf-sort
  - id: ksconf-xml-format
```

For general reference, here's a copy of what we frequently use for our repos.

```
- repo: https://github.com/pre-commit/pre-commit-hooks
  rev: v2.0.0
  hooks:
  - id: trailing-whitespace
    exclude: README.md
  - id: end-of-file-fixer
    exclude: README.md$
  - id: check-json
  - id: check-xml
  - id: check-ast
  - id: check-added-large-files
    args: [ '--maxkb=50' ]
  - id: check-merge-conflict
  - id: detect-private-key
  - id: mixed-line-ending
    args: [ '--fix=lf' ]
- repo: https://github.com/Kintyre/ksconf
  rev: v0.7.7
  hooks:
  - id: ksconf-check
  - id: ksconf-sort
```

(continues on next page)

(continued from previous page)

```
exclude: (props|logging)\.conf
- id: ksconf-xml-format
```

Tip: You should update rev to the most currently released stable version. Upgrading this frequently isn't typically necessary since these two operations are pretty basic and stable. However, it's still a good idea to review the change log to see what, if any, pre-commit functionality was updated.

Note: Sometimes pre-commit can get in the way.

Instead of disabling it entirely, it's often better to disable the specific rule that's causing an issue using the SKIP environmental variable. So for example, if intentionally adding a file over 50 Kb, a command like this will allow all the *other* rules to still run.

```
SKIP=check-added-large-file git commit -m "Refresh lookup files for bogus TA"
```

This and other tricks are fully documented in the [pre-commit docs](#). However, this comes up frequently enough that it's worth repeating here.

Should my version of ksconf and pre-commit plugins be the same?

If you're running both ksconf locally as well as the ksconf pre-commit plugin, then technically you have ksconf installed twice. That may sound less than ideal, but practically, this isn't a problem. As long as the version of the ksconf CLI tool is *close* to the rev listed in `.pre-commit-config.yaml`, then everything should work fine.

Our suggestion:

1. Keep versions in the same *major.minor* release range or bump the version every 6-12 months.
2. Check the changelog for any pre-commit related changes or compatibility concerns.

While keeping ksconf CLI versions in sync across your environment is recommended, it doesn't matter as much for the pre-commit plugin. Why?

1. The pre-commit plugin offers a small subset of overall ksconf functionality.
2. The exposed functionality is stable and changes infrequently.
3. Updating pre-commit too frequently may cause unnecessary delays if you have a large team or high number of git clones throughout your environment, as each one will have to wait and upgrade the next time pre-commit is kicked off.

3.8.2 Git configuration tweaks

Ksconf as external difftool

Use *ksconf diff* as an external *difftool* provider for **git**. Edit `~/.gitconfig` and add the following entries:

```
[difftool "ksconf"]
  cmd = "ksconf --force-color diff \"$LOCAL\" \"$REMOTE\" | less -R"
[difftool]
  prompt = false
[alias]
  ksdiff = "difftool --tool=ksconf"
```

Now you can run this new `git` alias to compare files in your directory using the `ksconf diff` feature instead of the default textual diff that `git` provides. This is especially helpful if the `ksconf-sort pre-commit` hook hasn't been enabled.

```
git ksdiff props.conf
```

Tip: Wonky version of `git`?

If you find yourself in the situation where `git-difftool` hasn't been fully installed correctly (or the Perl extensions are missing), then here's a workaround option for you.

```
ksconf diff <(git show HEAD:./props.conf) props.conf
```

Take note of the relative path prefix `./`. In practice, this can be problematic.

Stanza aware textual diffs

Make `git diff` show the 'stanza' on the @@ output lines.

Note: How does `git` know that?

Ever wonder how `git diff` is able to show you the name of the function or method where changes were made? This works for many programming languages out of the box. If you've ever spent much time looking at diffs, that additional context is invaluable. As it turns out, this is customizable by adding a stanza matching regular expression with a file pattern match.

Simply add the following settings to your `git` configuration:

```
[diff "conf"]
  xfuncname = "^(\\[.*\\])$"
```

Then register this new ability with specific file patterns using `git`'s `attributes` feature. Edit `~/.config/git/attributes` and add:

```
*.conf diff=conf
*.meta diff=conf
```

Note: Didn't work as expected?

Be aware that the location for your global-level attributes may be different. Use the following command to test if the settings have been applied.

```
git check-attr -a -- *.conf
```

Test to make sure the xfuncname attribute was set as expected:

```
git config diff.conf.xfuncname
```

3.9 Random

3.9.1 Typographic and Convention

Pronounced: k·s·knf

Capitalization:

Form	Acceptability factor
ksconf	Always lower for CLI. Generally preferred.
KSCONF	Okay for titles.
Ksconf	Title case is okay too.
KSConf	You'll see this, but weird.
KSconf	Just proper nouns capitalized
KsConf	No, except maybe in a class name?
Ksconf	Thought about it. No go! Reserved for ASCII art ONLY

I wrote this while laughing at my own lack of consistency.

– Lowell

3.9.2 How Splunk writes to conf files

Splunk does some counter intuitive thing when it writes to local conf files.

For example,

1. All conf file updates are automatically minimized. Splunk never has to write the entire contents because updates *only* happen to “local” files.
2. Modified stanzas are sometimes rewritten in place, and other times removed from the current position and moved to the bottom of the .conf file. This behavior appears to vary based on what REST endpoint is used to initiate the update.

3. New stanzas are written with attributes sorted lexicographically. When a stanza is updated in place, the modified attributes may be updated in place and new entries are typically added at the bottom of the stanza.
4. Sometimes boolean values persist in unexpected ways. Primarily this is because there's more than one way to represent them textually, and that textual representation is different than what's stored in default. Often, literal values are passed through a conf REST POST so they make it to disk, but when read, are translated into booleans.

Essentially, Splunk will always “minimize” the conf file at each update. This is because Splunk internally keeps track of the final representation of the entire stanza (in memory), and only when it's written to disk does Splunk care about the current contents of the local file. In fact, Splunk re-reads the conf file immediately before updating it. This is why, if you've made a local change and forgot to reload, Splunk will typically not lose your changes. (Unless you've updated the same attribute both places... I mean, it's not magic.)

Tip: Don't believe me? Try it yourself.

To prove that it works this way, simply find a saved search that you modified from any app that you installed. Look at the local conf file and observe your changes. Now, go edit the saved search and restore some attribute to its original value; the most obvious one here would be the search attribute, but that's tricky if it's multiple lines. Now, go look at the local conf file again. If you've updated it with *exactly* the same value, then that attribute will have been completely removed from the local file. This is in fact a neat trick that can be used to revert local changes to allow future updates to “pass-through” unimpeded. In SHC scenarios, this may be your only option to remove local settings.

Okay, so what's the value in having a *minimize* command if Splunk does this automatically every time it's makes a change? Well, simply put, because Splunk can't write to all local file locations. Splunk only writes to the local folders of system, etc/users, and etc/apps (and sometimes to deployment-apps app.conf local file, but that's a different topic).

Also, there are times where boolean values will show up in an unexpected manor because of how Splunk treats them internally. It isn't certain if this is a silly mistake in the default .conf files or a clever workaround to what's essentially a design flaw in the conf system. Either way, we suspect the user benefits. Because Splunk accepts more values as boolean than what it will write out, certain boolean values will always be explicitly stored in the conf files. This means that disabled and several other settings in savedsearches.conf always get explicitly written. How is that helpful? Well, imagine what would happen if you accidentally changed disabled = 1 in the global stanzas in savedsearches.conf. Well, *nothing* if all savedsearches have that values explicitly written. The point is this: there are times when repeating yourself isn't a bad thing. (Incidentally, this is the reason for the --preserve-key flag on the *minimize* command.)

3.9.3 Grandfather Paradox

The KSCONF Splunk app disadvantageously breaks its designed paradigm. Ksconf was designed to be the program that manages all your other apps, so by deploying ksconf as an app itself, we open up the possibility that ksconf could upgrade, deploy, or manage itself. Basically, it could cut off the

limb that it's standing on. Practically, this can get messy, especially if you're on Windows, where file locking is also likely to cause issues.

So sure, if you want to be picky, "Grandfather paradox" is probably the wrong analogy. Pull requests are welcome.

3.10 Contact

If you have questions, concerns, ideas about the product or how to make it better, please let us know!

Here are some ways to get in contact with us and other KSCONF users:

- Chat about [#ksconf](#) on Splunk's [Slack](#) channel.
- Email us at hello@kintyre.co for general inquiries, if you're interested in commercial support, or would like to fund new features.
- Ask a question on
 - [Splunk Answers](#)
 - [GitHub](#)

3.11 Command line reference

KSCONF supports the following CLI options:

3.11.1 ksconf

```
usage: ksconf [-h] [--version] [--force-color]
             {check,combine,diff,package,filter,promote,merge,minimize,snapshot,
             ↪sort,rest-export,rest-publish,unarchive,xml-format}
             ...

Ksconf: Kintyre Splunk CONFig tool

This utility handles a number of common Splunk app maintenance tasks in a small
and easy to deploy package. Specifically, this tool deals with many of the
nuances with storing Splunk apps in git and pointing live Splunk apps to a git
repository. Merging changes from the live system's (local) folder to the
version controlled (default) folder and dealing with more than one layer of
"default" are all supported tasks which are not native to Splunk.

positional arguments:
  {check,combine,diff,package,filter,promote,merge,minimize,snapshot,sort,rest-
  ↪export,rest-publish,unarchive,xml-format}
  check                Perform basic syntax and sanity checks on .conf files
  combine              Combine configuration files across multiple source
```

(continues on next page)

(continued from previous page)

	directories into a single destination directory. This allows for an arbitrary number of Splunk configuration layers to coexist within a single app. Useful in both ongoing merge and one-time ad-hoc use.
diff	Compare settings differences between two .conf files ignoring spacing and sort order
package	Create a Splunk app .spl file from a source directory
filter	A stanza-aware GREP tool for conf files
promote	Promote .conf settings between layers using either batch or interactive mode. Frequently this is used to promote conf changes made via the UI (stored in the 'local' folder) to a version-controlled directory, such as 'default'.
merge	Merge two or more .conf files
minimize	Minimize the target file by removing entries duplicated in the default conf(s)
snapshot	Snapshot .conf file directories into a JSON dump format
sort	Sort a Splunk .conf file creating a normalized format appropriate for version control
rest-export	Export .conf settings as a curl script to apply to a Splunk instance later (via REST)
rest-publish	Publish .conf settings to a live Splunk instance via REST
unarchive	Install or upgrade an existing app in a git-friendly and safe way
xml-format	Normalize XML view and nav files
optional arguments:	
-h, --help	show this help message and exit
--version	show program's version number and exit
--force-color	Force TTY color mode on. Useful if piping the output a color-aware pager, like 'less -R'

3.11.2 kskonf check

usage: kskonf check [-h] [--quiet] FILE [FILE ...]	
Provides basic syntax and sanity checking for Splunk's .conf files. Use Splunk's built-in 'btool check' for a more robust validation of attributes and values. Consider using this utility as part of a pre-commit hook.	
positional arguments:	
FILE	One or more configuration files to check. If '-' is given, then read a list of files to validate from standard input
optional arguments:	
-h, --help	show this help message and exit
--quiet, -q	Reduce the volume of output.

3.11.3 kscnf combine

```
usage: kscnf combine [-h] [--target TARGET] [-m {auto,dir.d,disable}]
                  [-I PATTERN] [-E PATTERN] [--dry-run] [--follow-symlink]
                  [--banner BANNER] [--disable-marker]
                  source [source ...]
```

Merge .conf settings from multiple source directories into a combined target directory. Configuration files can be stored in a '/etc/*.d' like directory structure and consolidated back into a single 'default' directory.

This command supports both one-time operations and recurring merge jobs. For example, this command can be used to combine all users' knowledge objects (stored in 'etc/users') after a server migration, or to merge a single user's settings after their account has been renamed. Recurring operations assume some type of external scheduler is being used. A best-effort is made to only write to target files as needed.

The 'combine' command takes your logical layers of configs (upstream, corporate, Splunk admin fixes, and power user knowledge objects, ...) expressed as individual folders and merges them all back into the single 'default' folder that Splunk reads from. One way to keep the 'default' folder up-to-date is using client-side git hooks.

No directory layout is mandatory, but taking advantages of the native-support for 'dir.d' layout works well for many uses cases. This idea is borrowed from the Unix System V concept where many services natively read their config files from '/etc/*.d' directories.

Version notes: dir.d was added in kscnf 0.8. Starting in 1.0 the default will switch to 'dir.d', so if you need the old behavior be sure to update your scripts.

positional arguments:

source	The source directory where configuration files will be merged from. When multiple source directories are provided, start with the most general and end with the specific; later sources will override values from the earlier ones. Supports wildcards so a typical Unix 'conf.d/##-NAME' directory structure works well.
--------	---

optional arguments:

-h, --help	show this help message and exit
--target TARGET, -t TARGET	Directory where the merged files will be stored. Typically either 'default' or 'local'
-m {auto,dir.d,disable}, --layer-method {auto,dir.d,disable}	Set the layer type used by SOURCE. Use 'dir.d' if you have directories like 'MyApp/default.d/##-layer-name', or use 'disable' to manage layers explicitly and avoid any accidental layer detection. By default, 'auto' mode will enable transparent switching between 'dir.d' and 'disable' (legacy) behavior.

(continues on next page)

(continued from previous page)

```

-I PATTERN, --include PATTERN
    Name or pattern of layers to include.
-E PATTERN, --exclude PATTERN
    Name or pattern of layers to exclude from the target.
--dry-run, -D
    Enable dry-run mode. Instead of writing to TARGET,
    preview changes as a 'diff'. If TARGET doesn't exist,
    then show the merged file.
--follow-symlink, -l
    Follow symbolic links pointing to directories.
    Symlinks to files are always followed.
--banner BANNER, -b BANNER
    A banner or warning comment added to the top of the
    TARGET file. Used to discourage Splunk admins from
    editing an auto-generated file.
--disable-marker
    Prevents the creation of or checking for the
    '.ksconf_controlled' marker file safety check. This
    file is typically used indicate that the destination
    folder is managed by ksconf. This option should be
    reserved for well-controlled batch processing
    scenarios.

```

3.11.4 ksconf diff

```
usage: ksconf diff [-h] [-o FILE] [--comments] CONF1 CONF2
```

Compares the content differences of two .conf files

This command ignores textual differences (like order, spacing, and comments) and focuses strictly on comparing stanzas, keys, and values. Note that spaces within any given value, will be compared. Multi-line fields are compared in a more [traditional](#)

'diff' output so that long saved searches and macros can be compared more easily.

positional arguments:

```

CONF1      Left side of the comparison
CONF2      Right side of the comparison

```

optional arguments:

```

-h, --help      show this help message and exit
-o FILE, --output FILE
                File where difference is stored. Defaults to standard
                out.
--comments, -C  Enable comparison of comments. (Unlikely to work
                consistently)

```

3.11.5 ksconf package

```
usage: ksconf package [-h] [-f SPL] [--app-name APP_NAME]
                    [--blocklist BLOCKLIST] [--allowlist ALLOWLIST]
```

(continues on next page)

(continued from previous page)

```

[-I PATTERN] [-E PATTERN] [--follow-symlink]
[--set-version VERSION] [--set-build BUILD]
[--allow-local | --block-local | --merge-local]
[--release-file RELEASE_FILE] [--hook-script COMMAND]
SOURCE

```

Create a Splunk app or add on tarball (.spl) file from an app directory. 'ksconf package' can do useful things like, exclude unwanted files, combine layers, set the application version and build number, drop or promote the 'local' directory into 'default'.

positional arguments:

SOURCE Source directory for the Splunk app.

optional arguments:

```

-h, --help                    show this help message and exit
-f SPL, --file SPL            Name of splunk app file (tarball) to create.
--app-name APP_NAME          Specify the top-level app folder name. If this is not
                             given, the app folder name is automatically extracted
                             from the basename of SOURCE.
--blocklist BLOCKLIST, -b BLOCKLIST
                             Pattern for files/directories to exclude. Can be given
                             multiple times. You can load multiple exclusions from
                             disk by using 'file://path' which can be used with
                             '.gitignore' for example. (Default includes: '.git*',
                             '*.py[co]', '__pycache__', '.DS_Store')
--allowlist ALLOWLIST, -w ALLOWLIST
                             Remove a pattern that was previously added to the
                             blocklist.
--follow-symlink, -l         Follow symbolic links pointing to directories.
                             Symlinks to files are always followed.
--set-version VERSION        Set application version. By default the application
                             version is read from default/app.conf
--set-build BUILD            Set application build number.
--allow-local                Allow the local folder to be kept. WARNING: This goes
                             against Splunk packaging practices, and will cause
                             AppInspect to fail. However, this option can be useful
                             for private package transfers between servers or
                             possibly for app backups.
--block-local                Block the local folder and local.meta from the
                             resulting SPL.
--merge-local                Merge any files in local into the default folder when
                             build the archive. This is the default behavior.

```

Layer filtering:

If the app being packaged includes multiple layers, these arguments can be used to control which ones should be included in the final app file. If no layer options are specified, then all layers will be included.

```

-I PATTERN, --include PATTERN
                             Name or pattern of layers to include.

```

(continues on next page)

(continued from previous page)

```
-E PATTERN, --exclude PATTERN
    Name or pattern of layers to exclude from the target.
```

Advanced Build Options:
The following options are for more advanced app building workflows.

```
--release-file RELEASE_FILE
    Write the path of the newly generated archive file
    (SPL) after the archive is written. This is useful in
    build scripts when the SPL contains variables so the
    final name may not be known ahead of time.
```

```
--hook-script COMMAND
    Run the given command or script. This is run after all
    layer have been combined, and local directory
    handling, but before blocklist cleanup. Therefore if
    this command produces any unwanted files they can be
    removed with a '--blocklist' entry. This can be used
    to install python packages, for example.
```

3.11.6 kskonf filter

```
usage: kskonf filter [-h] [-o FILE] [--comments] [--verbose]
    [--match {regex,wildcard,string}] [--ignore-case]
    [--invert-match] [--files-with-matches]
    [--count | --brief] [--stanza PATTERN]
    [--attr-present ATTR] [--keep-attrs WC-ATTR]
    [--reject-attrs WC-ATTR]
    CONF [CONF ...]
```

Filter the contents of a conf file in various ways. Stanzas can be included or excluded based on a provided filter or based on the presence or value of a key. Where possible, this command supports GREP-like arguments to bring a familiar feel.

positional arguments:
CONF Input conf file

optional arguments:
-h, --help show this help message and exit
-o FILE, --output FILE File where the filtered results are written. Defaults to standard out.
--comments, -C Preserve comments. Comments are discarded by default.
--verbose Enable additional output.
--match {regex,wildcard,string}, -m {regex,wildcard,string} Specify pattern matching mode. Defaults to 'wildcard' allowing for '*' and '?' matching. Use 'regex' for more power but watch out for shell escaping. Use 'string' to enable literal matching.
--ignore-case, -i Ignore case when comparing or matching strings. By

(continues on next page)

(continued from previous page)

```

--invert-match, -v    default matches are case-sensitive.
                    Invert match results. This can be used to show what
                    content does NOT match, or make a backup copy of
                    excluded content.

Output mode:
Select an alternate output mode. If any of the following options are used,
the stanza output is not shown.

--files-with-matches, -l    List files that match the given search criteria
--count, -c                Count matching stanzas
--brief, -b                List name of matching stanzas

Stanza selection:
Include or exclude entire stanzas using these filter options. All filter
options can be provided multiple times. If you have a long list of
filters, they can be saved in a file and referenced using the special
'file:/' prefix. One entry per line.

--stanza PATTERN          Match any stanza who's name matches the given pattern.
                        PATTERN supports bulk patterns via the 'file:/'
                        prefix.
--attr-present ATTR      Match any stanza that includes the ATTR attribute.
                        ATTR supports bulk attribute patterns via the
                        'file:/' prefix.

Attribute selection:
Include or exclude attributes passed through. By default, all attributes
are preserved. Allowlist (keep) operations are preformed before blacklist
(reject) operations.

--keep-attrs WC-ATTR     Select which attribute(s) will be preserved. This
                        space separated list of attributes indicates what to
                        preserve. Supports wildcards.
--reject-attrs WC-ATTR   Select which attribute(s) will be discarded. This
                        space separated list of attributes indicates what to
                        discard. Supports wildcards.

```

3.11.7 ksconf promote

```

usage: ksconf promote [-h] [--batch | --interactive | --summary] [--verbose]
                    [--match {regex,wildcard,string}] [--ignore-case]
                    [--invert-match] [--stanza PATTERN] [--force] [--keep]
                    [--keep-empty]
                    SOURCE TARGET

Propagate .conf settings applied in one file to another. Typically this is used
to move 'local' changes (made via the UI) into another layer, such as the

```

(continues on next page)

(continued from previous page)

'default' or a named 'default.d/50-xxxxx') folder.

Promote has two modes: batch and interactive. In batch mode, all changes are applied automatically and the (now empty) source file is removed. In interactive mode, the user is prompted to select stanzas to promote. This way local changes can be held without being promoted.

NOTE: Changes are **MOVED** not copied, unless '--keep' is used.

positional arguments:

SOURCE	The source configuration file to pull changes from. (Typically the 'local' conf file)
TARGET	Configuration file or directory to push the changes into. (Typically the 'default' folder)

optional arguments:

-h, --help	show this help message and exit
--batch, -b	Use batch mode where all configuration settings are automatically promoted. All changes are removed from source and applied to target. The source file will be removed unless '--keep-empty' is used.
--interactive, -i	Enable interactive mode where the user will be prompted to approve the promotion of specific stanzas and attributes. The user will be able to apply, skip, or edit the changes being promoted.
--summary, -s	Summarize content that could be promoted.
--verbose	Enable additional output.
--force, -f	Disable safety checks. Don't check to see if SOURCE and TARGET share the same basename.
--keep, -k	Keep conf settings in the source file. All changes will be copied into the TARGET file instead of being moved there. This is typically a bad idea since local always overrides default.
--keep-empty	Keep the source file, even if after the settings promotions the file has no content. By default, SOURCE will be removed after all content has been moved into TARGET. Splunk will re-create any necessary local files on the fly.

Automatic filtering options:

Include or exclude stanzas to promote using these filter options. Stanzas selected by these filters will be promoted.

All filter options can be provided multiple times.

If you have a long list of filters, they can be saved in a file and referenced using the special 'file://' prefix. One entry per line.

--match {regex,wildcard,string}, -m {regex,wildcard,string}	Specify pattern matching mode. Defaults to 'wildcard' allowing for '*' and '?' matching. Use 'regex' for more power but watch out for shell escaping. Use 'string' to enable literal matching.
---	--

(continues on next page)

(continued from previous page)

<code>--ignore-case</code>	Ignore case when comparing or matching strings. By default matches are case-sensitive.
<code>--invert-match, -v</code>	Invert match results. This can be used to prevent content from being promoted.
<code>--stanza PATTERN</code>	Promote any stanza with a name matching the given pattern. PATTERN supports bulk patterns via the 'file:/' prefix.

3.11.8 kskonf merge

```
usage: kskonf merge [-h] [--target FILE] [--ignore-missing] [--dry-run]
                [--banner BANNER]
                FILE [FILE ...]
```

Merge two or more .conf files into a single combined .conf file. This is similar to the way that Splunk logically combines the 'default' and 'local' folders at runtime.

positional arguments:

FILE	The source configuration file(s) to collect settings from.
------	--

optional arguments:

<code>-h, --help</code>	show this help message and exit
<code>--target FILE, -t FILE</code>	Save the merged configuration files to this target file. If not provided, the merged conf is written to standard output.
<code>--ignore-missing, -s</code>	Silently ignore any missing CONF files.
<code>--dry-run, -D</code>	Enable dry-run mode. Instead of writing to TARGET, preview changes in 'diff' format. If TARGET doesn't exist, then show the merged file.
<code>--banner BANNER, -b BANNER</code>	A banner or warning comment added to the top of the TARGET file. Used to discourage Splunk admins from editing an auto-generated file.

3.11.9 kskonf minimize

```
usage: kskonf minimize [-h] [--target TARGET] [--dry-run | --output OUTPUT]
                [--explode-default] [-k PRESERVE_KEY]
                CONF [CONF ...]
```

Minimize a conf file by removing any duplicated default settings. Reduce a local conf file to only your intended changes without manually tracking which entries you've edited. Minimizing local conf files makes your local customizations easier to read and often results in cleaner upgrades.

(continues on next page)

(continued from previous page)

```
positional arguments:
  CONF                The default configuration file(s) used to determine
                     what base settings are. The base settings determine
                     what is unnecessary to repeat in target file.

optional arguments:
  -h, --help          show this help message and exit
  --target TARGET, -t TARGET
                     The local file that you wish to remove duplicate
                     settings from. This file will be read from and then
                     replaced with a minimized version.
  --dry-run, -D       Enable dry-run mode. Instead of writing and minimizing
                     the TARGET file, preview what would be removed as a
                     'diff'.
  --output OUTPUT     Write the minimized output to a separate file instead
                     of updating TARGET.
  --explode-default, -E
                     Enable minimization across stanzas for special use-
                     cases. Helpful when dealing with stanzas downloaded
                     from a REST endpoint or 'btool list' output.
  -k PRESERVE_KEY, --preserve-key PRESERVE_KEY
                     Specify attributes that should always be kept.
```

3.11.10 ksconf snapshot

```
usage: ksconf snapshot [-h] [--output FILE] [--minimize] PATH [PATH ...]

Build a static snapshot of various configuration files stored within a
structured json export format. If the .conf files being captured are within a
standard Splunk directory structure, then certain metadata and namespace
information is assumed based on typical path locations. Individual apps or
conf files can be collected as well, but less metadata may be extracted.

positional arguments:
  PATH                Directory from which to load configuration files. All
                     .conf and .meta file are included recursively.

optional arguments:
  -h, --help          show this help message and exit
  --output FILE, -o FILE
                     Save the snapshot to the named files. If not provided,
                     the snapshot is written to standard output.
  --minimize          Reduce the size of the JSON output by removing
                     whitespace. Reduces readability.
```

3.11.11 kskonf sort

```
usage: kskonf sort [-h] [--target FILE | --inplace] [-F] [-q] [-n LINES]
              FILE [FILE ...]
```

Sort a Splunk .conf file. Sort has two modes: (1) by default, the sorted config file will be echoed to the screen. (2) the config files are updated in-place when the '-i' option is used.

Manually managed conf files can be protected against changes by adding a comment containing the string 'KSCONF-NO-SORT' to the top of any .conf file.

positional arguments:

FILE	Input file to sort, or standard input.
------	--

optional arguments:

-h, --help	show this help message and exit
--target FILE, -t FILE	File to write results to. Defaults to standard output.
--inplace, -i	Replace the input file with a sorted version. WARNING: This a potentially destructive operation that may move/remove comments.
-n LINES, --newlines LINES	Number of lines between stanzas.

In-place update arguments:

-F, --force	Force file sorting for all files, even for files containing the special 'KSCONF-NO-SORT' marker.
-q, --quiet	Reduce the output. Reports only updated or invalid files. This is useful for pre-commit hooks, for example.

3.11.12 kskonf rest-export

```
usage: kskonf rest-export [-h] [--output FILE] [--disable-auth-output]
                        [--pretty-print] [-u | -D] [--url URL] [--app APP]
                        [--user USER] [--owner OWNER] [--conf TYPE]
                        [--extra-args EXTRA_ARGS]
                        CONF [CONF ...]
```

Build an executable script of the stanzas in a configuration file that can be later applied to a running Splunk instance via the Splunkd REST endpoint.

This can be helpful when pushing complex props and transforms to an instance where you only have UI access and can't directly publish an app.

positional arguments:

(continues on next page)

(continued from previous page)

CONF	Configuration file(s) to export settings from.
optional arguments:	
-h, --help	show this help message and exit
--output FILE, -t FILE	Save the shell script output to this file. If not provided, the output is written to standard output.
-u, --update	Assume that the REST entities already exist. By default, output assumes stanzas are being created.
-D, --delete	Remove existing REST entities. This is a destructive operation. In this mode, stanza attributes are unnecessary and ignored. NOTE: This works for 'local' entities only; the default folder cannot be updated.
--url URL	URL of Splunkd. Default: https://localhost:8089
--app APP	Set the namespace (app name) for the endpoint
--user USER	Deprecated. Use --owner instead.
--owner OWNER	Set the object owner. Typically, the default of 'nobody' is ideal if you want to share the configurations at the app-level.
--conf TYPE	Explicitly set the configuration file type. By default, this is derived from CONF, but sometimes it's helpful to set this explicitly. Can be any valid Splunk conf file type. Examples include: 'app', 'props', 'tags', 'savedsearches', etc.
--extra-args EXTRA_ARGS	Extra arguments to pass to all CURL commands. Quote arguments on the command line to prevent confusion between arguments to kskonf vs curl.
Output Control:	
--disable-auth-output	Turn off sample login curl commands from the output.
--pretty-print, -p	Enable pretty-printing. Make shell output a bit more readable by splitting entries across lines.

3.11.13 kskonf rest-publish

```
usage: kskonf rest-publish [-h] [--conf TYPE] [-m META] [--url URL]
                          [--user USER] [--pass PASSWORD] [-k]
                          [--session-key SESSION_KEY] [--app APP]
                          [--owner OWNER] [--sharing {user,app,global}] [-D]
                          CONF [CONF ...]
```

Publish stanzas in a .conf file to a running Splunk instance via REST. This requires access to the HTTPS endpoint of Splunk. By default, kskonf will handle both the creation of new stanzas and the update of existing stanzas. This can be used to push full configuration stanzas where you only have REST access and can't directly publish an app. Only attributes present in the conf file are pushed. While this may seem obvious, this fact can have profound implications in certain situations, like when using this command for

(continues on next page)

(continued from previous page)

continuous updates. This means that it's possible for the source `.conf` to ultimately differ from what ends up on the server's `.conf` file. One way to avoid this, is to explicitly remove an object using `--delete` mode first, and then insert a new copy of the object. Of course, this means that the object will be unavailable. The other impact is that `diffs` only compares and shows a subset of attribute. Be aware, that for consistency, the `configs/conf-TYPE` endpoint is used for this command. Therefore, a reload may be required for the server to use the published config settings.

positional arguments:

`CONF` Configuration file(s) to export settings from.

optional arguments:

`-h, --help` show this help message and exit

`--conf TYPE` Explicitly set the configuration file type. By default, this is derived from `CONF`, but sometimes it's helpful to set this explicitly. Can be any valid Splunk conf file type. Examples include: `'app'`, `'props'`, `'tags'`, `'savedsearches'`, etc.

`-m META, --meta META` Specify one or more `.meta` files to determine the desired read & write ACLs, owner, and sharing for objects in the `CONF` file.

`--url URL` URL of Splunkd. Default: `https://localhost:8089`

`--user USER` Login username Splunkd. Default: `admin`

`--pass PASSWORD` Login password Splunkd. Default: `changeme`

`-k, --insecure` Disable SSL cert validation.

`--session-key SESSION_KEY`
Use an existing session token instead of using a username and password to login.

`--app APP` Set the namespace (app name) for the endpoint

`--owner OWNER` Set the user who owns the content. The default of `'nobody'` works well for app-level sharing.

`--sharing {user,app,global}`
Set the sharing mode.

`-D, --delete` Remove existing REST entities. This is a destructive operation. In this mode, stanza attributes are unnecessary. NOTE: This works for `'local'` entities only; the default folder cannot be updated.

3.11.14 ksconf unarchive

```
usage: ksconf unarchive [-h] [--dest DIR] [--app-name NAME]
                        [--default-dir DIR] [--exclude EXCLUDE] [--keep KEEP]
                        [--allow-local]
                        [--git-sanity-check {off,changed,untracked,ignored}]
                        [--git-mode {nochange,stage,commit}] [--no-edit]
                        [--git-commit-args GIT_COMMIT_ARGS]
                        SPL
```

Install or overwrite an existing app in a git-friendly way.

(continues on next page)

(continued from previous page)

If the app already exists, steps will be taken to upgrade it safely.

The 'default' folder can be redirected to another path (i.e., 'default.d/10-upstream' or other desirable path if you're using the 'ksconf combine' tool to manage extra layers).

positional arguments:

SPL The path to the archive to install.

optional arguments:

-h, --help show this help message and exit

--dest DIR Set the destination path where the archive will be extracted. By default, the current directory is used. Sane values include: etc/apps, etc/deployment-apps, and so on.

--app-name NAME The app name to use when expanding the archive. By default, the app name is taken from the archive as the top-level path included in the archive (by convention).

--default-dir DIR Name of the directory where the default contents will be stored. This is a useful feature for apps that use a dynamic default directory that's created and managed by the 'combine' mode.

--exclude EXCLUDE, -e EXCLUDE Add a file pattern to exclude from extraction. Splunk's pseudo-glob patterns are supported here. '*' for any non-directory match, '...' for ANY (including directories), and '?' for a single character.

--keep KEEP, -k KEEP Specify a pattern for files to preserve during an upgrade. Repeat this argument to keep multiple patterns.

--allow-local Allow local/* and local.meta files to be extracted from the archive.

--git-sanity-check {off,changed,untracked,ignored} By default, 'git status' is run on the destination folder to detect working tree or index modifications before the unarchive process start. Sanity check choices go from least restrictive to most thorough: 'off' prevents all safety checks. 'changed' aborts only upon local modifications to files tracked by git. 'untracked' (the default) looks for changed and untracked files. 'ignored' aborts if (any) local changes, untracked, or ignored files are found.

--git-mode {nochange,stage,commit} Set the desired level of git integration. The default mode is *stage*, where new, updated, or removed files are automatically handled for you. To prevent any 'git add' or 'git rm' commands from being run, pick the 'nochange' mode.

--no-edit Tell git to skip opening your editor on commit. By default, you will be prompted to review/edit the

(continues on next page)

(continued from previous page)

```
commit message. (Git Tip: Delete the content of the
default message to abort the commit.)
--git-commit-args GIT_COMMIT_ARGS, -G GIT_COMMIT_ARGS
Extra arguments to pass to 'git'
```

3.11.15 kskonf xml-format

```
usage: kskonf xml-format [-h] [--indent INDENT] [--quiet] FILE [FILE ...]
```

Normalize and apply consistent XML indentation and CDATA usage for XML dashboards and navigation files. Technically this could be used on *any* XML file, but certain element names specific to Splunk's simple XML dashboards are handled specially, and therefore could result in unusable results. The expected indentation level is guessed based on the first element indentation, but can be explicitly set if not detectable.

positional arguments:

```
FILE          One or more XML files to check. If '-' is given, then a
               list of files is read from standard input
```

optional arguments:

```
-h, --help    show this help message and exit
--indent INDENT Number of spaces. This is only used if indentation cannot
               be guessed from the existing file.
--quiet, -q   Reduce the volume of output.
```

3.12 Changelog

Note: Changes in master, but not released yet are marked as *DRAFT*.

3.12.1 Kskonf 0.8.0

Adds automatic layer detection support to the core library that's usable within multiple commands. Removed the deprecated zipapp deployment method.

v0.8-beta2 (2020-04-24)

- Removed support for building a standalone executable (zipapp). This packaging option was added in v0.4.3, and deprecated in v0.6.0, once the Splunk app install option became available. Yeah, I didn't use it much either!

v0.8-beta1 (2020-04-24)

- Add automatic layer support. Currently the two supported layer schemes are (1) explicit layers (really this will disable automatic layer detection), and (2) the `dir.d` format which uses the `default.d/##-layer-name` style directory support, which we previously promoted in the docs, but never really *fully* supported in a native way. This new `dir.d` directory layout support also allows for multiple `*.d` folders in a single tree (so not just `default.d`), and if your apps have different layer-points in different apps, it's all handled transparently. Currently support is limited to just the `ksconf combine` command but support for `unarchive` hasn't been completed yet. (This should be done before the 0.8.0 release.)
- Layer selection support was added to the `combine` command. This allows you to `--include` and `--exclude` layers as you see fit. See the docs for more details and examples of this new functionality. This works for both the new `dir.d` directories and the explicit layers, though moving to the `dir.d` format is highly encouraged.

3.12.2 Ksconf 0.7.x

New functionality, massive documentation improvements, metadata support, and Splunk app install fixes.

Release v0.7.8 (2020-06-19)

- New automatic promote mode is now available using CLI arguments! This allows stanzas to be selected for promotion from the CLI in batch and interactive modes. This implementation borrows (and shares code) with the `ksconf filter` command so hopefully the CLI arguments look familiar. It's possible to promote a single stanza, a stanza wildcard, regex or invert the matching logic and promote everything except for the named stanza (blocklist). Right now `--stanza` is the only supporting matching mode, but more can be added as needed. A huge thanks to [mthambipillai](#) for providing a pull-request with an initial implementation of this feature!
- Added a new summary output mode (`ksconf promote --summary`) that will provide a quick summary of what content could be promoted. This can be used along side the new `--stanza` filtering options to show the names of stanzas that can be promoted.
- Replaced insensitive terminology with race-neutral terms. Specifically the terms 'blacklist' and 'whitelist' have been replaced. NOTE: This does *not* change any CLI attributes, but in a few cases the standard output terminology is slightly different. Also terminology in `.conf` files couldn't be updated as that's controlled by Splunk.
- Fixed bug in the `unarchive` command where a `locale` folder was blocked as a local folder and where a nested `default` folder (nested under a Python package, for example) could get renamed if `--default-dir` was used, now only the top-most `default` folder is updated. Also fixed an unlikely bug triggered when `default/app.conf` is missing.
- Fixed bug with `minimize` when the required `--target` argument is not given. This now results in a reminder to the user rather than an unhandled exception.

- Splunk app packaging fix. Write access to the app was previously not granted due to a spelling mistake in the metadata file.

Release v0.7.7 (2020-03-05)

- Added new `--follow-symlink` option to the `combine` command so that input directory structures with symbolic links can be treated the same as proper directories.
- Corrected Windows issue where wildcard (glob) patterns weren't expanded by `for` check and `sort`. This is primarily a difference in how a proper shells (e.g., `bash`, `csh`, `zsh`) handle expansion natively vs `CMD` on Windows does not. However, since this is typically transparently handled by many CLI tools, we'll follow suite. (BTW, running `ksconf` from the `GIT Bash` prompt is a great alternative.) Only the most minimalistic expansion rules will be available, (so don't expect `{props,transforms,app}.conf` to work anytime soon), but this should be good enough for most use cases. Thanks to `SID800` for reporting this bug.
- Fixed issues with the `unarchive` command when `git` is not installed or an app is being unarchived (installed/upgrade) into a location not managed by `Git`. Note that additional output is now enabled when the `KSCONF_DEBUG` environmental variable is set (in lieu of a proper verbose mode). Bug report provided by `SID800`.
- Enhanced `ksconf --version` output to include `Git` executable path and version information; as well as a platform dump. (Helpful for future bug reporting.)
- Added feature to disable the marker file (safety check) automatically created by the `combine` command for use in automated processing workflows.
- Updated `pre-commit` documentation and sample configurations to use `rev` rather than `sha` as the means of identifying upstream tags or revisions. Recent releases of `pre-commit` will warn you about this during each run.
- Fixed a temporary file cleanup issue during certain in-place file replacement operations. (If you found any unexpected `*.tmp` files, this could have been the cause.)

Release v0.7.6 (2019-08-15)

- Fresh review and cleanup of all docs! (A huge thank you to `Brittany Barnett` for this massive undertaking)
- Fixed unhandled exception when encountering a global stanza in metadata files.
- Expand some error messages, sanity checks, and added a new session token (`--session-key`) authentication option for `rest-publish`.

Release v0.7.5 (2019-07-03)

- Fixed a long-term bug where the `diff` output of a single-line attribute change was incorrectly represented in the textual output of `'ksconf diff'` and the `diff` output in other commands. This resolves a combination of bugs, the first half of which was fixed in 0.7.3.

- Allow `make_docs` script to run on Windows, and other internal doc build process improvements.

Release v0.7.4 (2019-06-07)

- Inline the `six` module to avoid elusive bootstrapping cases where the module couldn't be found. This primarily impacts pre-commit users. The `ksconf.ext.*` prefix is being used for this, and any other inlined third party modules we may need in the future.
- Other minor docs fixes and internal non-visible changes.

Release v0.7.3 (2019-06-05)

- Added the new `ksconf xml-format` command.
 - The `ksconf xml-format` command brings format consistency to your XML representations of Simple XML dashboards and navigation files by fixing indentation automatically adding `<![CDATA[...]]>` blocks, as needed, to reduce the need for XML escaping, resulting in more readable source.
 - Additionally, a new pre-commit hook named `ksconf-xml-format` was added to leverage this new functionality. It looks specifically for xml views and navigation files based on path. This may also include Advanced XML, which hasn't been tested; So if you use Advanced XML, proceed with caution.
 - Note that this adds `lxml` as a packaging dependency which is needed for pre-commit hooks, but not strictly required at run time for other `ksconf` commands. This is NOT ideal, and may change in the future in attempts to keep `ksconf` as light-weight and standalone as possible. One possible alternative is setting up a different repo for pre-commit hooks. Python packaging and distribution tips welcome.
- Fixed data loss bug in `promote` (interactive mode only) and improved some UI text and prompts.
- Fixed colorization of `ksconf diff` output where certain lines failed to show up in the correct color.
- Fixed bug where debug tracebacks didn't work correctly on Python 2.7. (Enable using `KSCONF_DEBUG=1`.)
- Extended the output of `ksconf --version` to show the names and version of external modules, when present.
- Improved some resource allocation in corner cases.
- Tested with Splunk 7.3 (numeric similarity in version numbers is purely coincidental)

Attention: API BREAKAGE

The DiffOp output values for DIFF_OP_INSERT and DIFF_OP_DELETE have been changed in a backwards-compatible breaking way. The values of a and b were previously reversed for these two operations, leading to some code confusion.

Release v0.7.2 (2019-03-22)

- Fixed bug where filter would crash when doing stanza matching if global entries were present. Global stanzas can be matched by searching for a stanza named default.
- Fixed broken pre-commit issue that occurred for the v0.7.1 tag. This also kept setup.py from working if the six module wasn't already installed. Developers and pre-commit users were impacted.

Release v0.7.1 (2019-03-13)

- Additional fixes for UTF-8 BOM files which appear to happen more frequently with local files on Windows. This time some additional unit tests were added so hopefully there are few regressions in the future.
- Add the ignore-missing argument to *ksconf merge* to prevent errors when input files are absent. This allows bashisms `Some_App/{{default,local}}/savedsearches.conf` to work without errors if the local or default file is missing.
- Check for incorrect environment setup and suggest running `sourcing setSplunkEnv` to get a working environment. See #48 for more info.
- Minor improvements to some internal error handling, packaging, docs, and troubleshooting code.

Release v0.7.0 (2019-02-27)

Attention: For anyone who installed 0.6.x, we recommend a fresh install of the Splunk app due to packaging changes. This shouldn't be an issue in the future.

General changes:

- Added new *ksconf rest-publish* command that supersedes the use of `rest-export` for nearly every use case. Warning: No unit-testing has been created for this command yet, due to technical hurdles.
- Added *Cheat Sheet* to the docs.
- Massive doc cleanup of hundreds of typos and many expanded/clarified sections.

- Significant improvement to entrypoint handling and support for conditional inclusion of 3rd party libraries with sane behavior on import errors, and improved warnings. This information is conveniently viewable to the user via `ksconf --version`.
- Refactored internal diff logic and added additional safeties and unit tests. This includes improvements to TTY colorization which should avoid previous color leaks scenarios that were likely if unhandled exceptions occur.
- New support for metadata handling.
- CLI change for `rest-export`: The `--user` argument has been replaced with `--owner` to keep clean separation between the login account and object owners. (The old argument is still accept for now.)

Splunk app changes:

- Modified installation of python package installation. In previous releases, various `.dist-info` folders were created with version-specific names leading to a mismatch of package versions after upgrade. For this reason, we suggest that anyone who previously installed 0.6.x should do a fresh install.
- Changed Splunk app install script to `install.py` (it was `bootstrap_bin.py`). Hopefully this is more intuitive.
- Added Windows support to `install.py`.
- Now includes the Splunk Python SDK. Currently used for `rest-publish` but will eventually be used for additional functionality unique to the Splunk app.

3.12.3 Ksconf 0.6.x

Add deployment as a Splunk app for simplicity and significant docs cleanup.

Release v0.6.2 (2019-02-09)

- Massive rewrite and restructuring of the docs. Highlights include:
 - Reference material has been moved out of the user manual into a different top-level section.
 - Many new topics were added, such as
 - * *Ksconf as external difftool*
 - * *How Splunk writes to conf files*
 - * *Configuration layers*
 - * *What's so important about minimizing files?*
 - A new approach for CLI documentation. We're moving away from the **WALL OF TEXT** thing. (Yeah, it was really just the output from `--help`). That was limiting formatting, linking, and making the CLI output way too long.

- Refreshed Splunk app icons. Add missing alt icon.
- Several minor internal cleanups. Specifically the output of `--version` had a face lift.

Release v0.6.1 (2019-02-07)

- (Trivial) Fixed some small issues with the Splunk App (online AppInspect)

Release v0.6.0 (2019-02-06)

- Add initial support for building ksconf into a Splunk app.
 - App contains a local copy of the docs, helpful for anyone who's working offline.
 - Credit to Sarah Larson for the ksconf logos.
 - No ksconf functionality exposed to the Splunk UI at the moment.
- Docs/Sphinx improvements (more coming)
 - Begin work on cleaning up API docs.
 - Started converting various document pages into reStructuredText for greatly improved docs.
 - Improved PDF fonts and fixed a bunch of sphinx errors/warnings.
- Refactored the install docs into 2 parts. With the new ability to install ksconf as a Splunk app it's quite likely that most of the wonky corner cases will be less frequently needed, hence all the more exotic content was moved into the "Advanced Install Guide", tidying things up.

3.12.4 Ksconf 0.5.x

Add Python 3 support, new commands, support for external command plugins, tox and vagrant for testing.

Release v0.5.6 (2019-02-04)

- Fixes and improvements to the `filter` command. Found issue with processing from stdin, inconsistency in some CLI arguments, and finished implementation for various output modes.
- Add logo (fist attempt).

Release v0.5.5 (2019-01-28)

- New *ksconf filter* command added for slicing up a conf file into smaller pieces. Think of this as GREP that's stanza-aware. Can also allow or block attributes, if desirable.
- Expanded `rest-export` CLI capabilities to include a new `--delete` option, pretty-printing, and now supports stdin by allowing the user to explicitly set the file type using `--conf`.

- Refactored all CLI unittests for increased readability and long-term maintenance. Unit tests now can also be run individually as scripts from the command line.
- Minor tweaks to the snapshot output format, v0.2. This feature is still highly experimental.

Release v0.5.4 (2019-01-04)

- New commands added:
 - *ksconf snapshot* will dump a set of configuration files to a JSON formatted file. This can be used for incremental “snapshotting” of running Splunk apps to track changes overtime.
 - *ksconf rest-export* builds a series of custom curl commands that can be used to publish or update stanzas on a remote instance without file system access. This can be helpful when pushing configs to Splunk Cloud when all you have is REST (splunkd) access. This command is indented for interactive admin not batch operations.
- Added the concept of command maturity. A listing is available by running `ksconf --version`
- Fix typo in `KSCONF_DEBUG`.
- Resolving some build issues.
- Improved support for development/testing environments using Vagrant (fixes) and Docker (new). Thanks to Lars Jonsson for these enhancements.

Release v0.5.3 (2018-11-02)

- Fixed bug where `ksconf combine` could incorrectly order directories on certain file systems (like ext4), effectively ignoring priorities. Repeated runs may resulted in undefined behavior. Solved by explicitly sorting input paths forcing processing to be done in lexicographical order.
- Fixed more issues with handling files with BOM encodings. BOMs and encodings in general are NOT preserved by `ksconf`. If this is an issue for you, please add an enhancement issue.
- Add Python 3.7 support
- Expand install docs specifically for offline mode and some OS-specific notes.
- Enable additional tracebacks for CLI debugging by setting `KSCONF_DEBUG=1` in the environment.

Release v0.5.2 (2018-08-13)

- Expand CLI output for `--help` and `--version`
- Internal cleanup of CLI entry point module name. Now the `ksconf` CLI can be invoked as `python -m ksconf`, you know, for anyone who’s into that sort of thing.
- Minor docs and CI/testing improvements.

Release v0.5.1 (2018-06-28)

- Support external ksconf command plugins through custom *entry_points*, allowing for others to develop their own custom extensions as needed.
- Many internal changes: Refactoring of all CLI commands to use new *entry_points* as well as pave the way for future CLI unittest improvements.
- Docs cleanup / improvements.

Release v0.5.0 (2018-06-26)

- Python 3 support.
- Many bug fixes and improvements resulting from wider testing.

3.12.5 Ksconf 0.4.x

Ksconf 0.4.x switched to a modular code base, added build/release automation, PyPI package registration (installation via `pip install` and, online docs.

Release v0.4.10 (2018-06-26)

- Improve file handling to avoid “unclosed file” warnings. Impacted `parse_conf()`, `write_conf()`, and many unittest helpers.
- Update badges to report on the master branch only. (No need to highlight failures on feature or bug-fix branches.)

Release v0.4.9 (2018-06-05)

- Add some missing docs files

Release v0.4.8 (2018-06-05)

- Massive cleanup of docs: revamped install guide, added ‘standalone’ install procedure and developer-focused docs. Updated license handling.
- Updated docs configuration to dynamically pull in the ksconf version number.
- Using the classic ‘read-the-docs’ Sphinx theme.
- Added additional PyPi badges to README (GitHub home page).

Release v0.4.4-v0.4.1 (2018-06-04)

- Deployment and install fixes (It’s difficult to troubleshoot/test without making a new release!)

Release v0.4.3 (2018-06-04)

- Rename PyPI package `kintyre-splunk-conf`
- Add support for building a standalone executable (zipapp).
- Revamp install docs and location
- Add GitHub release for the standalone executable.

Release v0.4.2 (2018-06-04)

- Add `readthedocs.io` support

Release v0.4.1 (2018-06-04)

- Enable PyPI production package building

Release v0.4.0 (2018-05-19)

- Refactor entire code base. Switched from monolithic all-in-one file to clean-cut modules.
- Versioning is now discoverable via `ksconf --version`, and controlled via git tags (via `git describe --tags`).

Module layout

- `ksconf.conf.*` - Configuration file parsing, writing, comparing, and so on
- `ksconf.util.*` - Various helper functions
- `ksconf.archive` - Support for uncompressing Splunk apps (tgz/zip files)
- `ksconf.vc.git` - Version control support. Git is the only VC tool supported for now. (Possibly ever)
- `ksconf.commands.<CMD>` - Modules for specific CLI functions. I may make this extendable, eventually.

3.12.6 Ksconf 0.3.x

First public releases.

Release v0.3.2 (2018-04-24)

- Add AppVeyor for Windows platform testing
- Add codecov integration
- Created ConfFileProxy.dump()

Release v0.3.1 (2018-04-21)

- Setup automation via Travis CI
- Add code coverage

Release v0.3.0 (2018-04-21)

- Switched to semantic versioning.
- 0.3.0 feels representative of the code maturity.

3.12.7 Ksconf legacy releases

Ksconf started in a private Kintyre repo. There are no official releases; all git history has been rewritten.

Release legacy-v1.0.1 (2018-04-20)

- Fixes to blacklist support and many enhancements to ksconf unarchive.
- Introduces parsing profiles.
- Lots of bug fixes to various subcommands.
- Added automatic detection of ‘subcommands’ for CLI documentation helper script.

Release legacy-v1.0.0 (2018-04-16)

- This is the first public release. First work began Nov 2017 (as a simple conf ‘sort’ tool, which was imported from yet another repo.) Version history was extracted/rewritten/preserved as much as possible.
- Mostly stable features.
- Unit test coverage over 85%
- Includes pre-commit hook configuration (so that other repos can use this to run ksconf sort and ksconf check against their conf files.

3.13 Known issues

3.13.1 General

- File encoding issues: Byte order markers and specific encodings are NOT preserved. All files are encoding using UTF-8 upon update, which is Splunk's expected encoding.

3.13.2 Splunk app

- File cleanup issues after *KSCONF app for Splunk* upgrades (impacts versions prior to 0.7.0). Old `.dist-info` folders or other stale files may be left around after upgrades. If you encounter this issue, either uninstall and delete the `ksconf` directory or manually remove the old 'bin' folder and (re)upgrade to the latest version. The fix in 0.7.0 is to remove the version-specific portion of the folder name. (GH issue #37)

See more [confirmed bugs](#) in the issue tracker.

3.14 Advanced Installation Guide

The content in this document is a subsidiary to the [Installation Guide](#) because it became disorganized and the number of possible Python installation combinations and snags intensified. However, that culminated in the collection of excellent information that is provided here. Please remember, the Splunk app install approach was introduced to alleviate several of these issues.

A portion of this document is targeted at those who can't install packages as Admin or are forced to use Splunk's embedded Python. For everyone else, please start with the one-liner!

Tip: Do any of these words for phrases strike fear in your heart?

- pip
- pipenv
- virtualenv
- wheel
- pyenv (not the same as pyenv)
- python2.7 vs python27 vs py -27
- PYTHONPATH
- LD_LIBRARY
- RedHat Software Collections

If this list seems daunting, head over to [Install Splunk App](#). There's no shame in it.

Contents

- [Advanced Installation Guide](#)

- *Flowchart*
- *Installation*
 - * *Install from PyPI with PIP*
 - *Install ksconf into a virtual environment*
 - *Install ksconf system-wide*
 - * *CentOS (RedHat derived) distros*
 - *RedHat Software Collections*
 - * *Install the Wheel manually (offline mode)*
 - * *Install with Splunk's Python*
 - *On Linux or Mac*
 - *On Windows*
- *Offline installation*
 - * *Offline installation steps*
 - * *Offline installation of pip*
 - *Use pip without installing it*
- *Frequent gotchas*
 - * *PIP Install TLS Error*
 - * *No module named 'command.install'*
- *Troubleshooting*
 - * *Check Python version*
 - * *Check PIP Version*
 - * *Validate the install*
- *Resources*

3.14.1 Flowchart

(Unfinished; more of a brainstorm at this point...)

- Is Python installed? (OS level)
 - Is the version greater than 2.7? (Some early 2.7 version have quarks, but typically this is okay)
 - If Python 3.x, is it greater than 3.4? (I'd like to drop 3.4, but lots of old distros still have it.)
- Do you have admin access? (root/Administrator; or can you get it? How hard? Will you need

it each time you upgrade the kscnf?)

- Do you already have a large Python deployment or dependency? (If so, you'll probably be fine. Use `virtualenv`)
- Do you have any prior Python packaging or administration experience?
- Are you dealing with some vendor-specific solution?
 - Example: RedHat Software Collections – where they realize their software is way too old, so they try to make it possible to install newer version of things like Python, but since they aren't native or the default, you still end up jumping through a bunch of wonky hoops)
- Do you have Internet connectivity? (air gap or blocked outbound traffic, or proxy)
- Do you want to build/deploy your own kscnf extensions? If so, the Python package is a better option. (But at that point, you can probably already handle any packaging issues yourself.)

3.14.2 Installation

There are several ways to install kscnf. Technically, all standard Python packaging approaches should work just fine as there's no compiled code or external run-time dependencies so installation is fairly easy. However, for non-Python developers, there are some snags. Installation options are listed from the most easy and recommended, to more obscure and difficult:

Install from PyPI with PIP

The preferred installation method is to install via the standard Python package tool `pip`. Kscnf can be installed via the registered `kintyre-splunk-conf` package using the standard Python process.

There are 2 popular variations, depending on whether or not you would like to install for all users or test it locally.

Install kscnf into a virtual environment

Use this option if you don't have admin access

Installing kscnf with `virtualenv` is a great way to test the tool without requiring admin privileges and has many advantages for a production install. Here are the basic steps to get started.

Please change `venv` to a suitable path for your environment.

```
# Install Python virtualenv package (if not already installed)
pip install virtualenv

# Create and activate new 'venv' virtual environment
virtualenv venv
source venv/bin/activate
```

(continues on next page)

(continued from previous page)

```
pip install kintyre-splunk-conf
```

Note: Windows users

The above virtual environment activation should be run as `venv\Scripts\activate.bat`.

Install ksconf system-wide

Important: This requires admin access.

This is the absolute easiest install method where ‘ksconf’ is available to all users on the system but it requires root access and pip must be installed and up-to-date.

On Mac or Linux, run:

```
sudo pip install kintyre-splunk-conf
```

On Windows, run this command from an Administrator console.

```
pip install kintyre-splunk-conf
```

CentOS (RedHat derived) distros

```
# Enable the EPEL repo so that `pip` can be installed.
sudo yum install -y epel-release

# Install pip
sudo yum install -y python-pip

# Install ksconf (globally, for all users)
sudo pip install kintyre-splunk-conf
```

RedHat Software Collections

The following assumes the python27 software collection, but other version of Python are supported too. The initial setup and deployment of Software Collections is beyond the scope of this doc.

```
sudo scl enable python27 python -m pip install kintyre-splunk-conf
```

Hint: Missing pip?

If pip is missing from a RHSC, then install the following rpm.

```
yum install python27-python-pip
```

Unfortunately, the ksconf entrypoint script (in the bin folder) will not work correctly on it's own because it doesn't know about the scl environment, nor is it in the default PATH. To solve this, run the following:

```
sudo cat > /usr/local/bin/ksconf <<HERE
#!/bin/sh
source scl_source enable python27
exec /opt/rh/python27/root/usr/bin/ksconf "$@"
HERE
chmod +x /usr/local/bin/ksconf
```

Install the Wheel manually (offline mode)

Download the latest “Wheel” file from [PyPI](#), copy it to the destination server and install with pip.

Offline pip install:

```
pip install ~/Downloads/kintyre-splunk-conf-0.4.2-py2.py3-none-any.whl
```

Install with Splunk's Python

Deprecated since version 0.6.0: Don't do this anymore. Please use the [KSCONF App for Splunk](#) instead.

Splunk Enterprise 6.x and later installs an embedded Python 2.7 environment. However, Splunk does not provide packing tools (such as pip or the distutils standard library which is required to bootstrap install pip). For these reasons, it's typically easier and cleaner to install ksconf with the system provided Python. However, sometimes the system-provided Python environment is the wrong version, is missing (like on Windows), or security restrictions prevent the installation of additional packages. In such cases, Splunk's embedded Python becomes a beacon of hope.

On Linux or Mac

Download the latest “Wheel” file from [PyPI](#). The path to this download will be set in the pkg variable as shown below.

Setup the shell:

```
export SPLUNK_HOME=/opt/splunk
export pkg=~Downloads/kintyre_splunk_conf-0.4.9-py2.py3-none-any.whl
```

Run the following:

```
cd $SPLUNK_HOME
mkdir Kintyre
cd Kintyre
# Unzip the 'kconf' folder into SPLUNK_HOME/Kintyre
unzip "$pkg"

cat > $SPLUNK_HOME/bin/ksconf <<HERE
#!/bin/sh
export PYTHONPATH=$PYTHONPATH:$SPLUNK_HOME/Kintyre
exec $SPLUNK_HOME/bin/python -m ksconf \$*
HERE
chmod +x $SPLUNK_HOME/bin/ksconf
```

Test the install:

```
ksconf --version
```

On Windows

1. Open a browser and download the latest “Wheel” file from [PyPI](#).
2. Rename the .whl extension to .zip. (This may require showing file extensions in Explorer.)
3. Extract the zip file to a temporary folder. (This should create a folder named “ksconf”)
4. Create a new folder called “Kintyre” under the Splunk installation path (aka SPLUNK_HOME) By default, this is C:\Program Files\Splunk.
5. Copy the “ksconf” folder to %SPLUNK_HOME%\Kintyre.
6. Create a new batch file called ksconf.bat and paste in the following. Be sure to adjust for a non-standard %SPLUNK_HOME% value, if necessary.

```
@echo off
SET SPLUNK_HOME=C:\Program Files\Splunk
SET PYTHONPATH=%SPLUNK_HOME%\bin;%SPLUNK_HOME%\Python-2.7\Lib\site-packages\win32;
↪%SPLUNK_HOME%\Python-2.7\Lib\site-packages;%SPLUNK_HOME%\Python-2.7\Lib
SET PYTHONPATH=%PYTHONPATH%;%SPLUNK_HOME%\Kintyre
CALL "%SPLUNK_HOME%\bin\python.exe" -m ksconf %*
```

7. Move ksconf.bat to the Splunk\bin folder. (This assumes that %SPLUNK_HOME%/bin is part of your %PATH%. If not, add it, or find an appropriate install location.)
8. Test this by running ksconf --version from the command line.

3.14.3 Offline installation

Installing ksconf to an offline or network restricted computer requires three steps: (1) download the latest packages from the Internet to a staging location, (2) transfer the staged content (often as a zip file) to the restricted host, and (3) use pip to install packages from the staged copy. Fortunately, pip makes offline workflows quite easy to achieve. Pip can download a Python package with all

dependencies stored as wheels files into a single directory, and pip can be told to install from that directory instead of attempting to talk to the Internet.

The process of transferring these files is very organization-specific. The example below shows the creation of a tarball (since tar is universally available on Unix systems), but any acceptable method is fine. If security is a high concern, this step is frequently where safety checks are implemented: such as, antivirus scans, static code analysis, manual inspection, and/or comparison of cryptographic file hashes.

One additional use-case for this workflow, is to ensure the exact same version of all packages are deployed consistently across all servers and environments. Often, building a `requirements.txt` file with pip freeze, is a more appropriate solution. Alternatively, consider using pipenv lock for even more security benefits.

Offline installation steps

Important: Pip must be installed on the destination server for this process to work. If pip is NOT installed, see the *Offline installation of pip* section below.

Step 1: Use pip to download the latest package and their dependencies. Be sure to use the same version of Python that is running on destination machine.

```
# download packages
python2.7 -m pip download -d ksconf-packages kintyre-splunk-conf
```

A new directory named 'ksconf-packages' will be created and will contain the necessary *.whl files.

Step 2: Transfer the directory or archive to the remote computer. Insert whatever security and file copy procedures necessary for your organization.

```
# Compress directory (on staging computer)
tar -czvf ksconf-packages.tgz ksconf-packages

# Copy file using whatever means
scp ksconf-packages.tgz user@server:/tmp/ksconf-packages.tgz

# Extract the archive (on destination server)
tar -xzvf ksconf-packages.tgz
```

Step 3:

```
# Install ksconf package with pip
pip install --no-index --find-links=ksconf-packages kintyre-splunk-conf

# Test the installation
ksconf --version
```

The ksconf-packages folder can now be safely removed.

Offline installation of pip

Use the recommended pip install procedures listed elsewhere if possible. But if a remote bootstrap of pip is your only option, then here are the steps. (This process mirrors the steps above and can be combined, if needed.)

Step 1: Fetch bootstrap script and necessary wheels

```
mkdir ksconf-packages
curl https://bootstrap.pypa.io/get-pip.py -o ksconf-packages/get-pip.py
python2.7 -m pip download -d /tmp/my_packages pip setuptools wheel
```

The ksconf-packages folder should contain 1 script, and 3 wheel (*.whl) files.

Step 2: Archive and/or copy to offline server

Step 3: Bootstrap pip

```
sudo python get-pip.py --no-index --find-links=ksconf-packages/

# Test with
pip --version
```

Use pip without installing it

If you have a copy of the pip*.whl (wheel) file, then it can be executed directly by Python. This can be used to run pip without actually installing it, or for installing pip initially (bypassing the get-pip.py script step noted above.)

Here's an example of how this could work:

Step 1: Download the pip wheel on a machine where pip works, by running:

```
pip download pip -d .
```

This will create a file like pip-19.0.1-py2.py3-none-any.whl in the current working directory.

Step 2: Copy the pip wheel to another machine (likely where pip isn't installed.)

Step 3: Execute the wheel by running:

```
python pip-19.0.1-py2.py3-none-any.whl/pip list
```

Substitute the list command with whatever action you need (like install or whatever).

3.14.4 Frequent gotchas

PIP Install TLS Error

If pip throws an error message like the following:


```
There was a problem confirming the ssl certificate: [SSL: TLSV1_ALERT_PROTOCOL_VERSION]
↪tlsv1 alert protocol version
...
No matching distribution found for setuptools
```

The problem is likely caused by changes to PyPI website in April 2018 when support for TLS v1.0 and 1.1 were removed. Downloading new packages requires upgrading to a new version of pip. Like so:

Upgrade pip as follows:

```
curl https://bootstrap.pypa.io/get-pip.py | python
```

Note: Use `sudo python` above if not in a virtual environment.

Helpful links:

- [Not able to install Python packages \[SSL: TLSV1_ALERT_PROTOCOL_VERSION\]](#)
- [‘pip install’ fails for every package \(“Could not find a version that satisfies the requirement”\)](#)

No module named ‘command.install’

If, while trying to install pip or run a pip command you see the following error:

```
ImportError: No module named command.install
```

Likely this is because you are using a crippled version of Python; like the one that ships with Splunk. This won’t work. Either install the Splunk app package from Splunkbase or install using the OS-level Python.

3.14.5 Troubleshooting

Here are a few fact gathering type commands that may help you begin to track down problems.

Check Python version

Check your installed Python version by running:

```
python --version
```

Note that Linux distributions and Mac OS X that ship with multiple versions of Python may have renamed this to `python2`, `python2.7` or similar.

Check PIP Version

```
pip --version
```

If you are running a different Python interpreter version, you can instead run this as:

```
python2.7 -m pip --version
```

Validate the install

Confirm installation with the following command:

```
ksconf --version
```

If this works, it means that ksconf installed and is part of your PATH and should be useable everywhere in your system. Go forth and conquer!

If this doesn't work, here are a few things to try:

1. Check that your PATH is set correctly.
2. Try running ksconf as a "module" (sometimes works around a PATH issue). Run `python -m ksconf`
3. If you're running the Splunk app, try running the following:

```
cd $SPLUNK_HOME/etc/apps/ksconf/bin/lib
python -m ksconf --version
```

If this works, then the issue has something to do with your path.

It may be helpful to uninstall (remove) the Splunk app and reinstall from scratch.

3.14.6 Resources

- [Python packaging](#) docs provide a general overview on installing Python packages, how to install per-user vs install system-wide.
- [Install PIP](#) docs explain how to bootstrap or upgrade pip the Python packaging tool. Recent versions of Python come with this by default, but releases before Python 2.7.9 do not.

3.15 License

```
Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/
```

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

(continues on next page)

(continued from previous page)

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity

(continues on next page)

(continued from previous page)

on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
 - (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
 - (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
 - (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
 - (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and

(continues on next page)

(continued from previous page)

wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. **Submission of Contributions.** Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.
6. **Trademarks.** This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. **Disclaimer of Warranty.** Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. **Limitation of Liability.** In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.
9. **Accepting Warranty or Additional Liability.** While redistributing the Work or Derivative Works thereof, You may choose to offer,

(continues on next page)

(continued from previous page)

and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

Copyright 2019 Kintyre

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

3.16 API Reference

Note: As of now, no assumptions should be made about APIs remaining stable

KSCONF is first and foremost a CLI tool, so backwards incompatible changes are more of a concern for CLI breakage than for API breakage. That being said, there are a number of helpful features in the core ksconf Python module. So if anyone is interested in using the API, please feel free to do so, but let us know *how* you are using it and we'll find a way to keep the the important bits stable. We'd love to make it more clear what APIs are stable and which are likely to change.

As of right now, the general rule of thumb is this: Anything well-covered by the unit tests should be fairly safe to build on top of, but again, *ping us*.

3.16.1 ksconf

Subpackages

ksconf.commands package

Module contents

class `ksconf.commands.KsconfCmd(name)`

Bases: object

Ksconf command specification base class.

add_parser(*subparser*)

description = None

format = 'default'

help = None

launch(*args*)

Handle flow control between `pre_run()` / `run()` / `post_run()`

maturity = 'alpha'

parse_conf(*path*, *mode*='r', *profile*=None, *raw_exec*=False)

post_run(*args*, *exec_info*=None)

Any custom clean up work that needs done. Always called if `run()` was. Presence of `exc_info` indicates failure.

pre_run(*args*)

Pre-run hook. Any exceptions or true return code, prevents `run()`/`post_run()` from being called.

register_args(*parser*)

This function is passed the

run(*args*)

Actual work happens here. Return code should be an `EXIT_CODE_*` from `consts`.

version_extra = None

class `ksconf.commands.ConfDirProxy(name, mode, parse_profile=None)`

Bases: object

get_file(*relpath*)

class `ksconf.commands.ConfFileProxy(name, mode, stream=None, parse_profile=None, is_file=None)`

Bases: object

close()

data

dump(*data*, ***kwargs*)

exists()

is_file()

load(*profile*=None)

readable()

reset()

set_parser_option(kwargs)**

Setting a key to None will remove that setting.

stream

unlink()

writable()

class `ksconf.commands.ConfFileType(mode='r', action='open', parse_profile=None, accept_dir=False)`

Bases: object

Factory for creating conf file object types; returns a lazy-loader ConfFile proxy class

Started from `argparse.FileType()` and then changed everything. With our use case, it's often necessary to delay writing, or read before writing to a conf file (depending on whether or not `--dry-run` mode is enabled, for example.)

Instances of `FileType` are typically passed as `type=` arguments to the `ArgumentParser.add_argument()` method.

Parameters

- **mode** (str) – How the file is to be opened. Accepts “r”, “w”, and “r+”.
- **action** (str) – Determine how much work should be handled during argument parsing vs handed off to the caller. Supports ‘none’, ‘open’, ‘load’. Full descriptions below.
- **parse_profile** – parsing configuration settings passed along to the parser
- **accept_dir** (bool) – Should the CLI accept a directory of config files instead of an individual file. Defaults to *False*.

Values for action

Action	Description
none	No preparation or testing is done on the filename.
open	Ensure the file exists and can be opened.
load	Ensure the file can be opened and parsed successfully.

Once invoked, instances of this class will return a `ConfFileProxy` object, or a `ConfDirProxy` object if a directory is passed in via the CLI.

`ksconf.commands.dedent` (*text*)

Remove any common leading whitespace from every line in *text*.

This can be used to make triple-quoted strings line up with the left edge of the display, while still presenting them in the source code in indented form.

Note that tabs and spaces are both treated as whitespace, but they are not equal: the lines ”hello” and “thello” are considered to have no common leading whitespace. (This behaviour is new in Python 2.5; older versions of this module incorrectly expanded tabs before searching for common leading whitespace.)

```
ksconf.commands.get_all_ksconf_cmds(on_error='warn')
```

```
ksconf.commands.get_entrypoints
```

```
ksconf.commands.add_splunkd_access_args(parser)
```

```
ksconf.commands.add_splunkd_namespace(parser)
```

ksconf.conf package

Submodules

ksconf.conf.delta module

```
class ksconf.conf.delta.DiffGlobal(type)
```

Bases: tuple

type

Alias for field number 0

```
class ksconf.conf.delta.DiffHeader(name, mtime=None)
```

Bases: object

detect_mtime()

```
class ksconf.conf.delta.DiffOp(tag, location, a, b)
```

Bases: tuple

a

Alias for field number 2

b

Alias for field number 3

location

Alias for field number 1

tag

Alias for field number 0

```
class ksconf.conf.delta.DiffStanza(type, stanza)
```

Bases: tuple

stanza

Alias for field number 1

type

Alias for field number 0

class `ksconf.conf.delta.DiffStzKey`(*type, stanza, key*)

Bases: tuple

key

Alias for field number 2

stanza

Alias for field number 1

type

Alias for field number 0

`ksconf.conf.delta.compare_cfgs`(*a, b, allow_level0=True*)

Return list of 5-tuples describing how to turn a into b.

Note: The *Opcode* tags borrowed from SequenceMatcher class in the difflib standard Python module.

Each tuple takes the form:

(tag, location, a, b)

tag:

Value	Meaning
'replace'	same element in both, but different values.
'delete'	remove value b
'insert'	insert value a
'equal'	same values in both

location is a tuple that can take the following forms:

Tuple form	Description
(0)	Global file level context (e.g., both files are the same)
(1, <i>stanza</i>)	Stanzas are the same, or completely different (no shared keys)
(2, <i>stanza, key</i>)	Key level, indicating

Possible alternatives:

<https://dictdiffer.readthedocs.io/en/latest/#dictdiffer.patch>

`ksconf.conf.delta.compare_stanzas`(*a, b, stanza_name*)

`ksconf.conf.delta.is_equal`(*delta*)

Is the delta output show that the compared objects are identical

`ksconf.conf.delta.reduce_stanza`(*stanza, keep_attrs*)

Pre-process a stanzas so that only a common set of keys will be compared. :param stanza: Stanzas containing attributes and values :type stanza: dict :param keep_attrs: Listing of :type keep_attrs: (list, set, tuple, dict) :return: a reduced copy of stanza.

`ksconf.conf.delta.show_diff(stream, diffs, headers=None)`

`ksconf.conf.delta.show_text_diff(stream, a, b)`

`ksconf.conf.delta.summarize_cfg_diffs(delta, stream)`

Summarize a delta into a human readable format. The input *delta* is in the format produced by the `compare_cfgs()` function.

ksconf.conf.merge module

`ksconf.conf.merge.merge_conf_dicts(*dicts)`

`ksconf.conf.merge.merge_conf_files(dest, configs, dry_run=False, banner_comment=None)`

ksconf.conf.parser module

Parse and write Splunk's .conf files

According to this doc:

<https://docs.splunk.com/Documentation/Splunk/7.2.3/Admin/Howtoeditaconfigurationfile>

1. Comments must start at the beginning of a line (#)
2. Comments may not be after a stanza name or on an attribute's value
3. Supporting encoding is UTF-8 (and therefore ASCII too)

exception `ksconf.conf.parser.ConfParserException`

Bases: `Exception`

exception `ksconf.conf.parser.DuplicateKeyException`

Bases: `ksconf.conf.parser.ConfParserException`

exception `ksconf.conf.parser.DuplicateStanzaException`

Bases: `ksconf.conf.parser.ConfParserException`

class `ksconf.conf.parser.Token`

Bases: `object`

Immutable token object. `deepcopy` returns the same object

`ksconf.conf.parser.conf_attr_boolean(value)`

`ksconf.conf.parser.cont_handler(iterable, continue_re=re.compile('^(.*)\\\\\\\\$'), breaker='\\n')`

Look for trailing backslashes (“\\”) which indicate a value for an attribute is split across multiple lines. This function will group such lines together, and pass all other lines through as-is. Note that the continuation character must be the very last character on the line, trailing whitespace is not allowed.

Parameters

- **iterable** (*iter*) – lines from a configuration file
- **continue_re** – regular expression to detect the continuation character
- **breaker** – joining string when combining continued lines into a single string. Default ‘\n’

Returns lines of text

Return type `str`

`ksconf.conf.parser.detect_by_bom(path)`

`ksconf.conf.parser.inject_section_comments(section, prepend=None, append=None)`

`ksconf.conf.parser.parse_conf(stream, profile={'dup_key': 'overwrite', 'dup_stanza': 'exception', 'keep_comments': True, 'strict': True}, encoding=None)`

Parse a .conf file. This is a wrapper around `parse_conf_stream()` that allows filenames or stream to be passed in.

Parameters

- **stream** (`str`, `file`) – the path to a configuration file or open file-like object to be parsed
- **profile** – parsing configuration settings
- **encoding** – Defaults to the system default, “uft-8”

Returns a mapping of the stanza and attributes. The resulting output is accessible as `[stanaza][attribute] -> value`

Return type `dict`

`ksconf.conf.parser.parse_conf_stream(stream, keys_lower=False, handle_conts=True, keep_comments=False, dup_stanza='exception', dup_key='overwrite', strict=False)`

`ksconf.conf.parser.section_reader(stream, section_re=re.compile('^[\\s\\t]*\\[(.*)\\]\\s*$'))`

This generator break a configuration file stream into sections. Each section contains a name and a list of text lines held within that section.

Sections that have no entries may be dropped. Any lines before the first section are send back with the section name of `None`.

Parameters

- **stream** (`file`) – configuration file input stream
- **section_re** – regular expression for detecting stanza headers

Returns sections in the form of `(section_name, lines_of_text)`

Return type `tuple`

`ksconf.conf.parser.smart_write_conf(filename, conf, stanza_delim='\n', sort=True, temp_suffix='.tmp')`

```
ksconf.conf.parser.splitup_kvpairs(lines,      comments_re=re.compile('^\\s*[#;]'),
                                   keep_comments=False, strict=False)
Break up 'attribute=value' entries in a configuration file.
```

Parameters

- **lines** (iter) – the body of a stanza containing associated attributes and values
- **comments_re** – Regular expression used to detect comments.
- **keep_comments** (bool, optional) – Should comments be preserved in the output. Defaults to *False*.
- **strict** (bool, optional) – Should unknown content in the stanza stop processing. Defaults to *False* allowing “junk” to be silently ignored allowing for a best-effort parse.

Returns iterable of (attribute,value) tuples

```
class ksconf.conf.parser.update_conf(conf_path,  profile={'dup_key':      'overwrite',
               'dup_stanza':      'exception',  'keep_comments':
               True,             'strict':      True},    encoding=None,
                                   make_missing=False)
```

Bases: object

Context manager that allows for simple in-place updates to conf files

keys()

update(*args, **kwargs)

```
ksconf.conf.parser.write_conf(stream, conf, stanza_delim='\n', sort=True)
```

```
ksconf.conf.parser.write_conf_stream(stream, conf, stanza_delim='\n', sort=True)
```

Module contents

ksconf.util package

Submodules

ksconf.util.compare module

```
ksconf.util.compare.file_compare(fn1, fn2)
```

```
ksconf.util.compare.fileobj_compare(f1, f2)
```

ksconf.util.completers module

```
ksconf.util.completers.DirectoriesCompleter(*args, **kwargs)
```

`ksconf.util.completers.FilesCompleter(*args, **kwargs)`

`ksconf.util.completers.autocomplete(*args, **kwargs)`

ksconf.util.file module

class `ksconf.util.file.ReluctantWriter(path, *args, **kwargs)`

Bases: object

Context manager to intelligently handle updates to an existing file. New content is written to a temp file, and then compared to the current file's content. The file will be overwritten only if the contents changed.

`ksconf.util.file.dir_exists(directory)`

Ensure that the directory exists

`ksconf.util.file.expand_glob_list(iterable, do_sort=False)`

`ksconf.util.file.file_fingerprint(path, compare_to=None)`

`ksconf.util.file.file_hash(path, algorithm='sha256')`

`ksconf.util.file.match_bwlist(value, bwlist, escape=True)`

`ksconf.util.file.relwalk(top, topdown=True, onerror=None, followlinks=False)`

Relative path walker Like `os.walk()` except that it doesn't include the "top" prefix in the resulting 'dirpath'.

`ksconf.util.file.smart_copy(src, dest)`

Copy (overwrite) file only if the contents have changed.

`ksconf.util.file.which(cmd, mode=1, path=None)`

Given a command, mode, and a PATH string, return the path which conforms to the given mode on the PATH, or None if there is no such file. *mode* defaults to `os.F_OK | os.X_OK`. *path* defaults to the result of `os.environ.get("PATH")`, or can be overridden with a custom search path.

ksconf.util.rest module

`ksconf.util.rest.build_rest_namespace(base, owner=None, app=None)`

`ksconf.util.rest.build_rest_url(base, service, owner=None, app=None)`

ksconf.util.terminal module

class `ksconf.util.terminal.TermColor(stream)`

Bases: object

Simple color setting helper class that's a context manager wrapper around a stream. This ensure that the color is always reset at the end of a session.

color(*codes)

reset()

write(content)

ksconf.util.terminal.**tty_color**(stream, *codes)

Module contents

ksconf.util.**debug_traceback**()

If the 'KSCONF_DEBUG' environmental variable is set, then show a stack trace.

ksconf.vc package

Submodules

ksconf.vc.git module

class ksconf.vc.git.**GitCmdOutput**(cmd, returncode, stdout, stderr, lines)

Bases: tuple

cmd

Alias for field number 0

lines

Alias for field number 4

returncode

Alias for field number 1

stderr

Alias for field number 3

stdout

Alias for field number 2

exception ksconf.vc.git.**GitNotAvailable**

Bases: Exception

ksconf.vc.git.**git_cmd**(args, shell=False, cwd=None, capture_std=True, encoding='utf-8')

ksconf.vc.git.**git_cmd_iterable**(args, iterable, cwd=None, cmd_len=1024)

ksconf.vc.git.**git_is_clean**(path=None, check_untracked=True, check_ignored=False)

ksconf.vc.git.**git_is_working_tree**(path=None)

ksconf.vc.git.**git_ls_files**(path, *modifiers)

ksconf.vc.git.**git_status_summary**(path)

ksconf.vc.git.**git_status_ui**(path, *args)

`ksconf.vc.git.git_version()`

Module contents

Submodules

ksconf.archive module

`ksconf.archive.GenArchFile`

alias of `ksconf.archive.GenericArchiveEntry`

`ksconf.archive.extract_archive(archive_name, extract_filter=None)`

`ksconf.archive.gaf_filter_name_like(pattern)`

`ksconf.archive.gen_arch_file_remapper(iterable, mapping)`

`ksconf.archive.sanity_checker(iterable)`

ksconf.consts module

ksconf.layer module

class `ksconf.layer.DirectLayerRoot(config=None)`

Bases: `ksconf.layer.LayerRootBase`

A very simple direct LayerRoot implementation that relies on all layer paths to be explicitly given without any automatic detection mechanisms. You can think of this as the legacy implementation.

add_layer(path)

order_layers()

class `ksconf.layer.DotDLayerRoot(config=None)`

Bases: `ksconf.layer.LayerRootBase`

class `Layer(name, root, physical, logical, config, file_cls, prune_points=None)`

Bases: `ksconf.layer.Layer`

prune_points

walk()

apply_filter(layer_filter)

Apply a destructive filter to all layers. `layer_filter(layer)` will be called one for each layer, if the filter returns True then the layer is kept. Root layers are always kept.

layer_regex = re.compile('(P<layer>\\d\\d-[\\w_.-]+)')

list_layers()

mount_regex = re.compile('(P<realname>[\\w_.-]+)\\.d\$')

order_layers()

set_root(*root*)

Set a root path, and auto discover all '.d' directories.

Note: We currently only support '.d/<layer>' directories, so something like *default.d/10-props.conf* won't be handled here.

class `ksconf.layer.LayerConfig`

Bases: object

exception `ksconf.layer.LayerException`

Bases: Exception

class `ksconf.layer.LayerFilter`

Bases: object

add_rule(*action*, *pattern*)

evaluate(*layer*)

class `ksconf.layer.LayerRootBase(config=None)`

Bases: object

All 'path's here are relative to the ROOT.

class `File(layer, relative_path, size=None, mtime=None)`

Bases: object

layer

logical_path

mtime

physical_path

relative_path

size

class `Layer(name, root, physical, logical, config, file_cls)`

Bases: object

Basic layer Container: Connects logical and physical paths.

config

get_file(*path*)

Return file object (by logical path), if it exists in this layer.

list_files()

logical_path

name

physical_path

root

`walk()`

`add_layer(layer, do_sort=True)`

`apply_filter(layer_filter)`

Apply a destructive filter to all layers. `layer_filter(layer)` will be called one for each layer, if the filter returns True then the layer is kept. Root layers are always kept.

`get_file(path)`

return all layers associated with the given relative path.

`get_path_layers(path)`

`list_files()`

Return a list of logical paths.

`list_layer_names()`

`list_layers()`

`order_layers()`

exception `ksconf.layer.LayerUsageException`

Bases: `ksconf.layer.LayerException`

`ksconf.layer.path_in_layer(layer, path, sep='/')`

Check to see if path exist within layer. Returns either None, or the path without the shared prefix with layer.

`ksconf.layer.run_oldshool(args)`

`ksconf.setup_entrypoints` module

Defines all command prompt entry points for CLI actions

This is a silly hack that serves 2 purposes:

- (1) It works around an apparent Python 3.4/3.5 bug on Windows where `[options.entry_point]` in `setup.cfg` is ignored hence 'ksconf' isn't installed as a console script and custom `ksconf_*` entry points are not available. (So no CLI commands are available)
- (2) **It allows for fallback mechanism when**
 - (a) running unit tests (can happen before install)
 - (b) if entrypoints or `pkg_resources` are not available at run time (Splunk's embedded python)

class `ksconf.setup_entrypoints.Ep(name, module_name, object_name)`

Bases: tuple

module_name

Alias for field number 1

name

Alias for field number 0

object_name

Alias for field number 2

class `ksconf.setup_entrypoints.LocalEntryPoint(data)`

Bases: object

Bare minimum stand-in for `entrypoints.EntryPoint`**load()**`ksconf.setup_entrypoints.debug()``ksconf.setup_entrypoints.get_entrypoints_fallback(group)``ksconf.setup_entrypoints.get_entrypoints_setup()`**ksconf.xmlformat module****class** `ksconf.xmlformat.FileReadlinesCache`

Bases: object

Silly class as a hacky workaround for CDATA detection...

static `convert_filename(filename)``readlines(filename)`**class** `ksconf.xmlformat.SplunkSimpleXmlFormatter`

Bases: object

static `CDATA_tags(elem, tags)`

Expand text to CDATA, if it isn't already.

classmethod `expand_tags(elem, tags)`Keep `<elem></elem>` instead of shortening to `<elem/>`**classmethod** `format_xml(src, dest, default_indent=2)`**static** `guess_indent(elem, default=2)`**classmethod** `indent_tree(elem, level=0, indent=2)``keep_tags = {'default', 'earliest', 'fieldset', 'label', 'latest', 'option', 'search', 'set'}`**Module contents**

ksconf - Kintyre Splunk CONFig tool

Design goals:

- Multi-purpose go-to `.conf` tool.
- Dependability
- Simplicity
- No eternal dependencies (single source file, if possible; or packable as single file.)

- Stable CLI
- Good scripting interface for deployment scripts and/or git hooks

exception `ksconf.KsconfPluginWarning`

Bases: `Warning`

CHAPTER 4

Indices and tables

- `genindex`
- `modindex`
- `search`

Bibliography

[SPLKDOC1] <https://docs.splunk.com/Documentation/Splunk/7.2.3/Admin/Configurationfiledirectories>

k

- ksconf, 111
- ksconf.archive, 108
- ksconf.commands, 99
- ksconf.conf, 105
- ksconf.conf.delta, 101
- ksconf.conf.merge, 103
- ksconf.conf.parser, 103
- ksconf.consts, 108
- ksconf.layer, 108
- ksconf.setup_entrypoints, 110
- ksconf.util, 107
- ksconf.util.compare, 105
- ksconf.util.completers, 105
- ksconf.util.file, 106
- ksconf.util.rest, 106
- ksconf.util.terminal, 106
- ksconf.vc, 108
- ksconf.vc.git, 107
- ksconf.xmlformat, 111

A

ksconf.conf.delta.DiffOp attribute), 101
 add_layer() (*ksconf.layer.DirectLayerRoot* method), 108
 add_layer() (*ksconf.layer.LayerRootBase* method), 110
 add_parser() (*ksconf.commands.KsconfCmd* method), 99
 add_rule() (*ksconf.layer.LayerFilter* method), 109
 add_splunkd_access_args() (in module *ksconf.commands*), 101
 add_splunkd_namespace() (in module *ksconf.commands*), 101
 apply_filter() (*ksconf.layer.DotDLayerRoot* method), 108
 apply_filter() (*ksconf.layer.LayerRootBase* method), 110
 autocomplete() (in module *ksconf.util.completers*), 106

B

b (*ksconf.conf.delta.DiffOp* attribute), 101
 build_rest_namespace() (in module *ksconf.util.rest*), 106
 build_rest_url() (in module *ksconf.util.rest*), 106

C

cdata_tags() (*ksconf.xmlformat.SplunkSimpleXmlFormat* static method), 111
 close() (*ksconf.commands.ConfFileProxy* method), 99
 cmd (*ksconf.vc.git.GitCmdOutput* attribute), 107

color() (*ksconf.util.terminal.TermColor* method), 106
 compare_cfgs() (in module *ksconf.conf.delta*), 102
 compare_stanzas() (in module *ksconf.conf.delta*), 102
 conf_attr_boolean() (in module *ksconf.conf.parser*), 103
 ConfDirProxy (class in *ksconf.commands*), 99
 ConfFileProxy (class in *ksconf.commands*), 99
 ConfFileType (class in *ksconf.commands*), 100
 config (*ksconf.layer.LayerRootBase.Layer* attribute), 109
 ConfParserException, 103
 cont_handler() (in module *ksconf.conf.parser*), 103
 convert_filename() (*ksconf.xmlformat.FileReadlinesCache* static method), 111

D

data (*ksconf.commands.ConfFileProxy* attribute), 99
 debug() (in module *ksconf.setup_entrypoints*), 111
 debug_traceback() (in module *ksconf.util*), 107
 dedent() (in module *ksconf.commands*), 100
 description (*ksconf.commands.KsconfCmd* attribute), 99
 detect_by_bom() (in module *ksconf.conf.parser*), 104
 detect_mtime() (*ksconf.conf.delta.DiffHeader* method), 101
 DiffGlobal (class in *ksconf.conf.delta*), 101
 DiffHeader (class in *ksconf.conf.delta*), 101

- DiffOp (class in *ksconf.conf.delta*), 101
 - DiffStanza (class in *ksconf.conf.delta*), 101
 - DiffStzKey (class in *ksconf.conf.delta*), 101
 - dir_exists() (in module *ksconf.util.file*), 106
 - DirectLayerRoot (class in *ksconf.layer*), 108
 - DirectoriesCompleter() (in module *ksconf.util.completers*), 105
 - DotDLayerRoot (class in *ksconf.layer*), 108
 - DotDLayerRoot.Layer (class in *ksconf.layer*), 108
 - dump() (*ksconf.commands.ConfFileProxy* method), 99
 - DuplicateKeyException, 103
 - DuplicateStanzaException, 103
- E**
- Ep (class in *ksconf.setup_entrypoints*), 110
 - evaluate() (*ksconf.layer.LayerFilter* method), 109
 - exists() (*ksconf.commands.ConfFileProxy* method), 99
 - expand_glob_list() (in module *ksconf.util.file*), 106
 - expand_tags() (*ksconf.xmlformat.SplunkSimpleXmlFormatter* class method), 111
 - extract_archive() (in module *ksconf.archive*), 108
- F**
- file_compare() (in module *ksconf.util.compare*), 105
 - file_fingerprint() (in module *ksconf.util.file*), 106
 - file_hash() (in module *ksconf.util.file*), 106
 - fileobj_compare() (in module *ksconf.util.compare*), 105
 - FileReadlinesCache (class in *ksconf.xmlformat*), 111
 - FilesCompleter() (in module *ksconf.util.completers*), 105
 - format (*ksconf.commands.KsconfCmd* attribute), 99
 - format_xml() (*ksconf.xmlformat.SplunkSimpleXmlFormatter* class method), 111
- G**
- gaf_filter_name_like() (in module *ksconf.archive*), 108
 - gen_arch_file_remapper() (in module *ksconf.archive*), 108
 - GenArchFile (in module *ksconf.archive*), 108
 - get_all_ksconf_cmds() (in module *ksconf.commands*), 101
 - get_entrypoints (in module *ksconf.commands*), 101
 - get_entrypoints_fallback() (in module *ksconf.setup_entrypoints*), 111
 - get_entrypoints_setup() (in module *ksconf.setup_entrypoints*), 111
 - get_file() (*ksconf.commands.ConfDirProxy* method), 99
 - get_file() (*ksconf.layer.LayerRootBase* method), 110
 - get_file() (*ksconf.layer.LayerRootBase.Layer* method), 109
 - get_path_layers() (*ksconf.layer.LayerRootBase* method), 110
 - git_cmd() (in module *ksconf.vc.git*), 107
 - git_cmd_iterable() (in module *ksconf.vc.git*), 107
 - git_clean() (in module *ksconf.vc.git*), 107
 - git_is_working_tree() (in module *ksconf.vc.git*), 107
 - git_ls_files() (in module *ksconf.vc.git*), 107
 - git_status_summary() (in module *ksconf.vc.git*), 107
 - git_status_ui() (in module *ksconf.vc.git*), 107
 - git_version() (in module *ksconf.vc.git*), 107
 - GitCmdOutput (class in *ksconf.vc.git*), 107
 - GitNotAvailable, 107
 - guess_indent() (*ksconf.xmlformat.SplunkSimpleXmlFormatter* static method), 111
- H**
- help (*ksconf.commands.KsconfCmd* attribute), 99
- I**
- indent_tree() (*ksconf.xmlformat.SplunkSimpleXmlFormatter* class method), 111
 - inject_section_comments() (in module *ksconf.conf.parser*), 104
 - is_equal() (in module *ksconf.conf.delta*), 102
 - is_file() (*ksconf.commands.ConfFileProxy* method), 99

K

keep_tags (*ksconf.xmlformat.SplunkSimpleXmlFormatter* attribute), 111

key (*ksconf.conf.delta.DiffStzKey* attribute), 102

keys() (*ksconf.conf.parser.update_conf* method), 105

ksconf (module), 111

ksconf.archive (module), 108

ksconf.commands (module), 99

ksconf.conf (module), 105

ksconf.conf.delta (module), 101

ksconf.conf.merge (module), 103

ksconf.conf.parser (module), 103

ksconf.consts (module), 108

ksconf.layer (module), 108

ksconf.setup_entrypoints (module), 110

ksconf.util (module), 107

ksconf.util.compare (module), 105

ksconf.util.completers (module), 105

ksconf.util.file (module), 106

ksconf.util.rest (module), 106

ksconf.util.terminal (module), 106

ksconf.vc (module), 108

ksconf.vc.git (module), 107

ksconf.xmlformat (module), 111

KsconfCmd (class in *ksconf.commands*), 99

KsconfPluginWarning, 112

L

launch() (*ksconf.commands.KsconfCmd* method), 99

layer (*ksconf.layer.LayerRootBase.File* attribute), 109

layer_regex (*ksconf.layer.DotDLayerRoot* attribute), 108

LayerConfig (class in *ksconf.layer*), 109

LayerException, 109

LayerFilter (class in *ksconf.layer*), 109

LayerRootBase (class in *ksconf.layer*), 109

LayerRootBase.File (class in *ksconf.layer*), 109

LayerRootBase.Layer (class in *ksconf.layer*), 109

LayerUsageException, 110

lines (*ksconf.vc.git.GitCmdOutput* attribute), 107

list_files() (*ksconf.layer.LayerRootBase* method), 110

list_files() (*ksconf.layer.LayerRootBase.Layer* method), 109

list_layer_names() (*ksconf.layer.LayerRootBase* method), 110

list_layers() (*ksconf.layer.DotDLayerRoot* method), 108

list_layers() (*ksconf.layer.LayerRootBase* method), 110

load() (*ksconf.commands.ConfigFileProxy* method), 99

load() (*ksconf.setup_entrypoints.LocalEntryPoint* method), 111

LocalEntryPoint (class in *ksconf.setup_entrypoints*), 111

location (*ksconf.conf.delta.DiffOp* attribute), 101

logical_path (*ksconf.layer.LayerRootBase.File* attribute), 109

logical_path (*ksconf.layer.LayerRootBase.Layer* attribute), 109

M

match_bwlist() (in module *ksconf.util.file*), 106

maturity (*ksconf.commands.KsconfCmd* attribute), 99

merge_conf_dicts() (in module *ksconf.conf.merge*), 103

merge_conf_files() (in module *ksconf.conf.merge*), 103

module_name (*ksconf.setup_entrypoints.Ep* attribute), 110

mount_regex (*ksconf.layer.DotDLayerRoot* attribute), 108

mtime (*ksconf.layer.LayerRootBase.File* attribute), 109

N

name (*ksconf.layer.LayerRootBase.Layer* attribute), 109

name (*ksconf.setup_entrypoints.Ep* attribute), 110

O

object_name (*ksconf.setup_entrypoints.Ep* attribute), 110

order_layers() (*ksconf.layer.DirectLayerRoot* method), 108

order_layers() (*ksconf.layer.DotDLayerRoot* method), 108

order_layers() (*ksconf.layer.LayerRootBase* method), 110

P

`parse_conf()` (in module `ksconf.conf.parser`), 104
`parse_conf()` (`ksconf.commands.KsconfCmd` method), 99
`parse_conf_stream()` (in module `ksconf.conf.parser`), 104
`path_in_layer()` (in module `ksconf.layer`), 110
`physical_path` (`ksconf.layer.LayerRootBase.File` attribute), 109
`physical_path` (`ksconf.layer.LayerRootBase.Layer` attribute), 109
`post_run()` (`ksconf.commands.KsconfCmd` method), 99
`pre_run()` (`ksconf.commands.KsconfCmd` method), 99
`prune_points` (`ksconf.layer.DotDLayerRoot.Layer` attribute), 108

R

`readable()` (`ksconf.commands.ConfFileProxy` method), 99
`readlines()` (`ksconf.xmlformat.FileReadlinesCache` method), 111
`reduce_stanza()` (in module `ksconf.conf.delta`), 102
`register_args()` (`ksconf.commands.KsconfCmd` method), 99
`relative_path` (`ksconf.layer.LayerRootBase.File` attribute), 109
`ReluctantWriter` (class in `ksconf.util.file`), 106
`relwalk()` (in module `ksconf.util.file`), 106
`reset()` (`ksconf.commands.ConfFileProxy` method), 100
`reset()` (`ksconf.util.terminal.TermColor` method), 107
`returncode` (`ksconf.vc.git.GitCmdOutput` attribute), 107
`root` (`ksconf.layer.LayerRootBase.Layer` attribute), 109
`run()` (`ksconf.commands.KsconfCmd` method), 99
`run_oldshool()` (in module `ksconf.layer`), 110

S

`sanity_checker()` (in module `ksconf.archive`), 108
`section_reader()` (in module `ksconf.conf.parser`), 104

`set_parser_option()` (`ksconf.commands.ConfFileProxy` method), 100
`set_root()` (`ksconf.layer.DotDLayerRoot` method), 109
`show_diff()` (in module `ksconf.conf.delta`), 102
`show_text_diff()` (in module `ksconf.conf.delta`), 103
`size` (`ksconf.layer.LayerRootBase.File` attribute), 109
`smart_copy()` (in module `ksconf.util.file`), 106
`smart_write_conf()` (in module `ksconf.conf.parser`), 104
`splitup_kvpairs()` (in module `ksconf.conf.parser`), 104
`SplunkSimpleXmlFormatter` (class in `ksconf.xmlformat`), 111
`stanza` (`ksconf.conf.delta.DiffStanza` attribute), 101
`stanza` (`ksconf.conf.delta.DiffStzKey` attribute), 102
`stderr` (`ksconf.vc.git.GitCmdOutput` attribute), 107
`stdout` (`ksconf.vc.git.GitCmdOutput` attribute), 107
`stream` (`ksconf.commands.ConfFileProxy` attribute), 100
`summarize_cfg_diffs()` (in module `ksconf.conf.delta`), 103

T

`tag` (`ksconf.conf.delta.DiffOp` attribute), 101
`TermColor` (class in `ksconf.util.terminal`), 106
`Token` (class in `ksconf.conf.parser`), 103
`tty_color()` (in module `ksconf.util.terminal`), 107
`type` (`ksconf.conf.delta.DiffGlobal` attribute), 101
`type` (`ksconf.conf.delta.DiffStanza` attribute), 101
`type` (`ksconf.conf.delta.DiffStzKey` attribute), 102

U

`unlink()` (`ksconf.commands.ConfFileProxy` method), 100
`update()` (`ksconf.conf.parser.update_conf` method), 105
`update_conf` (class in `ksconf.conf.parser`), 105

V

`version_extra` (*ksconf.commands.KsconfCmd* attribute), 99

W

`walk()` (*ksconf.layer.DotDLayerRoot.Layer* method), 108

`walk()` (*ksconf.layer.LayerRootBase.Layer* method), 109

`which()` (in module *ksconf.util.file*), 106

`writable()` (*ksconf.commands.ConfigFileProxy* method), 100

`write()` (*ksconf.util.terminal.TermColor* method), 107

`write_conf()` (in module *ksconf.conf.parser*), 105

`write_conf_stream()` (in module *ksconf.conf.parser*), 105